







# Molded Case Circuit Breakers and Switches Terminals for Type NZM 10...-NA

1	2	3	4	5	6	7
General info	Maximum Rated Current  Amps	Conductor Cross-section Range and Material	Type suffix <sup>1)</sup> Sets of three terminals ordered with breaker or molded case switch: O = Mounted on Top U = Mounted on Bottom	Price  \$	Type  Individual terminals supplied separately for field mounting	Price  \$
<b>Terminals</b>						
Supplied with 3 terminal covers (Type <b>H-NZM 10</b> ) and an insulating plate onto which the circuit breaker is mounted.		600	2 x AWG 2 – 500 kcmil Cu/Al	+ K2X240IP-NZM 10-O + K2X240IP-NZM 10-U	See Price List	See Price List
Supplied with 1 terminal cover (Type <b>H-NZM 10</b> ) and an insulating plate onto which the circuit breaker is mounted.		600	2 x AWG 2 – 500 kcmil Cu/Al	—	See Price List	K2X240IP-NZM 10 <sup>2)</sup>
Supplied with 1 terminal cover (Type <b>H-NZM 10</b> )		600	2 x AWG 2 – 500 kcmil Cu/Al	—	See Price List	K2X240-NZM 10 <sup>2)</sup>
Single cable clamp terminal. Not supplied with terminal cover. Suitable terminal cover is Type <b>HH-NZM 10</b>		350	250 – 500 kcmil Cu only	+ K300-NZM 10-O + K300-NZM 10-U	See Price List	K300-NZM 10
Double cable clamp terminal. Not supplied with cover. Suitable terminal cover is Type <b>HH-NZM 10</b>		500	2 x AWG 3/0 – 250 kcmil Cu only	+K2x120-NZM 10-O +K2x120-NZM 10-U	See Price List	K2x120-NZM 10
<b>Terminal Covers</b>						
<b>Single pole terminal cover.</b> Supplied standard with Type <b>K2x240(IP)</b> terminals. Can be used for bolt-on or cable lug connection.				+H-NZM 10-O +H-NZM 10-U	See Price List	H-NZM 10
One piece, 3 pole terminal cover. Suitable for use with Type <b>K300</b> or <b>K2x120</b> terminals.				+HH-NZM 10-O +HH-NZM 10-U	See Price List	HH-NZM 10

**NZM 10** Circuit Breakers and Molded Case Switches are supplied standard with bolt-on connection. For Line and Load field-wiring terminals for cable connection, select from information specified above. All terminals can be ordered factory installed with the device (Column 4) or separately for field installation (Column 6).

Ordering information:  
Specify Type from Columns 4 or 6. Example: **+ K2 x 240IP-NZM 10-O**

1) When ordering with the device (Column 4), the Type suffix specifies which side should be equipped with terminals:  
 Suffix **O** - Denotes a set of three terminals and covers mounted on the top.  
 Suffix **U** - Denotes a set of three terminals and covers mounted on the bottom.  
 Note: All Moeller Electric Molded Case Circuit Breakers, including the **NZM 10**, are UL listed and CSA certified for reverse feed connection and can therefore be fed optionally from top or bottom.

2) Complete set of three (for top or bottom) Type **K2x240(IP)** terminals for field installation (column 6) consists of the following:  
 - Qty. of one **K2x240IP** terminal, which is supplied with one **H-NZM 10** terminal cover and one insulating plate.  
 - Qty. of two **K2x240** terminals, which are supplied each with one **H-NZM 10** terminal cover.

