

Contact sequence
Front plate no.



F5 908

Main conducting paths
No. of poles



Auxiliary contacts



Max. motor rating

AC-23A
400/415 V
50-60 Hz

Rated uninterrupted current

I_u

A

Design

Protection type

Part no.
Article no.


Price
see price list

Std. pack


Main switches, maintenance switches

According to IEC/EN 60204-1, VDE 0113 Part 1; with red rotary handle and yellow locking collar, lockable in 0 position

As Emergency-Stop device



1 0 2 0 3 0 4 0 5 0 6 0 7 0 8 0 9 0 10 0 11 0 12 0



1 0 2 0 3 0 4 0 5 0 6 0 7 0 8 0 9 0 10 0 11 0 12 0



1 0 2 0 3 0 4 0 5 0 6 0 7 0 8 0 9 0 10 0 11 0 12 0 13 0 14 0 15 0 16 0

Front plate no.	Main conducting paths No. of poles	Auxiliary contacts	Max. motor rating	Rated uninterrupted current	Design	Protection type	Part no. Article no.	Price see price list	Std. pack
	3 + N	0	0	55	160	Flush mounting	Front IP65	P5-160/EA/SVB/N 280924	1 off
	3 + N	0	0	55	160	Rear mounting	Front IP65	P5-160/V/SVB/N 280930	
	3 + N	0	0	90	250	Flush mounting	Front IP65	P5-250/EA/SVB/N 280938	
	3 + N	0	0	90	250	Rear mounting	Front IP65	P5-250/V/SVB/N 280944	
	3 + N	0	0	110	315	Flush mounting	Front IP65	P5-315/EA/SVB/N 280952	
	3 + N	0	0	110	315	Rear mounting	Front IP65	P5-315/V/SVB/N 280958	
	6	0	0	6.5	20	Surface mounting	IP65	T0-3-8342/I1/SVB 207159	
	6	0	0	6.5	20	Flush mounting	Front IP65	T0-3-8342/EA/SVB 029382	
	6	0	0	6.5	20	Rear mounting	Front IP65	T0-3-8342/V/SVB 034128	
	6	0	0	13	32	Surface mounting	IP65	T3-3-8342/I2/SVB 207208	
	6	0	0	13	32	Flush mounting	Front IP65	T3-3-8342/EA/SVB 071326	
	6	0	0	13	32	Rear mounting	Front IP65	T3-3-8342/V/SVB 076072	
	6	0	0	22	63	Surface mounting	IP65	T5B-3-8342/I4/SVB 207242	
	6	0	0	22	63	Flush mounting	Front IP65	T5B-3-8342/EA/SVB 092308	
	6	0	0	22	63	Rear mounting	Front IP65	T5B-3-8342/V/SVB 092300	
	6	0	0	30	100	Surface mounting	IP65	T5-3-8342/I5/SVB 207279	
	6	0	0	30	100	Flush mounting	Front IP65	T5-3-8342/EA/SVB 096383	
	6	0	0	30	100	Rear mounting	Front IP65	T5-3-8342/V/SVB 096381	
	8	0	0	6.5	20	Surface mounting	IP65	T0-4-8344/I1/SVB 207163	
	8	0	0	6.5	20	Flush mounting	Front IP65	T0-4-8344/EA/SVB 008267	
	8	0	0	6.5	20	Rear mounting	Front IP65	T0-4-8344/V/SVB 014007	
	8	0	0	13	32	Surface mounting	IP65	T3-4-8344/I2/SVB 207212	
	8	0	0	13	32	Flush mounting	Front IP65	T3-4-8344/EA/SVB 008964	
	8	0	0	13	32	Rear mounting	Front IP65	T3-4-8344/V/SVB 020598	
	8	0	0	22	63	Surface mounting	IP65	T5B-4-8344/I4/SVB 207248	
	8	0	0	22	63	Flush mounting	Front IP65	T5B-4-8344/EA/SVB 092062	
	8	0	0	22	63	Rear mounting	Front IP65	T5B-4-8344/V/SVB 092056	
	8	0	0	30	100	Surface mounting	IP65	T5-4-8344/I5/SVB ¹⁾ 207283	
	8	0	0	30	100	Flush mounting	Front IP65	T5-4-8344/EA/SVB 095961	

Notes

¹⁾ Rated uninterrupted current max. 95 A