





Load current switches, main switches, maintenance/repair switches

http://catalog.moeller.net

Moeller HPL0211-2007/2008

T, P **xCommand**

Contact sequence Front plate no.	Main conducting paths No. of poles	Auxiliary contacts	Max. motor rating	Rated uninter- rupted current	Design	Protection type	Part no. Article no.	Price see price list	Std. pack
 FS 908			AC-23A 400/415 V 50-60 Hz	I_u A					
	I N/O	I N/O L N/C	P kW						
Main switches, maintenance switches									
With black rotary handle and locking collar, lockable in the 0 position									
Without Emergency-Stop function									
	3 + N	0 0	50	100	Surface mounting	IP65 <small>totally insulated</small>	P3-100/I5/SVB-SW/N 207376		1 off
	3 + N	0 0	50	100	Flush mounting	Front IP65	P3-100/EA/SVB-SW/N 022263		
	3 + N	0 0	50	100	Rear mounting	Front IP65	P3-100/V/SVB-SW/N 027009		
	3 + N	0 0	45	125	Flush mounting	Front IP65	P5-125/EA/SVB-SW/N 280913		
	3 + N	0 0	45	125	Rear mounting	Front IP65	P5-125/V/SVB-SW/N 280919		
	3 + N	0 0	55	160	Flush mounting	Front IP65	P5-160/EA/SVB-SW/N 280927		
	3 + N	0 0	55	160	Rear mounting	Front IP65	P5-160/V/SVB-SW/N 280933		
	3 + N	0 0	90	250	Flush mounting	Front IP65	P5-250/EA/SVB-SW/N 280941		
	3 + N	0 0	90	250	Rear mounting	Front IP65	P5-250/V/SVB-SW/N 280947		
	3 + N	0 0	110	315	Flush mounting	Front IP65	P5-315/EA/SVB-SW/N 280955		
	6	0 0	6.5	20	Surface mounting	IP65 <small>totally insulated</small>	T0-3-8342/I1/SVB-SW 207160		
	6	0 0	6.5	20	Flush mounting	Front IP65	T0-3-8342/EA/SVB-SW 031755		
	6	0 0	6.5	20	Rear mounting	Front IP65	T0-3-8342/V/SVB-SW 036501		
	6	0 0	13	32	Surface mounting	IP65 <small>totally insulated</small>	T3-3-8342/I2/SVB-SW 207209		
	6	0 0	13	32	Flush mounting	Front IP65	T3-3-8342/EA/SVB-SW 073699		
	6	0 0	13	32	Rear mounting	Front IP65	T3-3-8342/V/SVB-SW 078445		
	6	0 0	22	63	Surface mounting	IP65 <small>totally insulated</small>	T5B-3-8342/I4/SVB-SW 207243		
	6	0 0	22	63	Flush mounting	Front IP65	T5B-3-8342/EA/SVB-SW 092307		
	6	0 0	22	63	Rear mounting	Front IP65	T5B-3-8342/V/SVB-SW 092299		
	6	0 0	30	100	Surface mounting	IP65 <small>totally insulated</small>	T5-3-8342/I5/SVB-SW 207280		
	6	0 0	30	100	Flush mounting	Front IP65	T5-3-8342/EA/SVB-SW 096382		
	6	0 0	30	100	Rear mounting	Front IP65	T5-3-8342/V/SVB-SW 096380		
	8	0 0	6.5	20	Surface mounting	IP65 <small>totally insulated</small>	T0-4-8344/I1/SVB-SW 207164		
	8	0 0	6.5	20	Flush mounting	Front IP65	T0-4-8344/EA/SVB-SW 008268		
	8	0 0	13	32	Surface mounting	IP65 <small>totally insulated</small>	T3-4-8344/I2/SVB-SW 207213		
	8	0 0	13	32	Flush mounting	Front IP65	T3-4-8344/EA/SVB-SW 008965		
	8	0 0	13	32	Rear mounting	Front IP65	T3-4-8344/V/SVB-SW 008967		
	8	0 0	22	63	Surface mounting	IP65 <small>totally insulated</small>	T5B-4-8344/I4/SVB-SW 207249		
	8	0 0	22	63	Flush mounting	Front IP65	T5B-4-8344/EA/SVB-SW 092061		
	8	0 0	30	100	Surface mounting	IP65 <small>totally insulated</small>	T5-4-8344/I5/SVB-SW¹⁾ 207284		

Notes ¹⁾ Rated uninterrupted current max. 95 A

Rotary switches, switch-disconnectors

