



Connection, on rear, 3p, 1 page, size 1

Part no. NZM1-XKR
266734

General specifications			
Product name		Eaton Moeller series NZM connection type	
Part no.		NZM1-XKR	
EAN		4015082667344	
Product Length/Depth		140 millimetre	
Product height		35 millimetre	
Product width		60 millimetre	
Product weight		0.393 kilogram	
Compliances		RoHS conform IEC	
Product Tradename		NZM	
Product Type		Accessories	
Product Sub Type		Connection type	
Delivery program			
Type		Accessory Connection on rear Terminal	
Number of poles		Three-pole	
Amperage Rating		≤ 160 A	
Frame		NZM1	
Suitable for		Three-pole Aluminum cable lug Copper cable lugs	
Used with		NZM1, PN1, N(S)1	
Technical Data - Mechanical - Terminals			
Terminal capacity (stranded cable)		10 mm ² - 35 mm ² (2x) 2.5 mm ² - 25 mm ² (2x) 2.5 mm ² - 25 mm ² (1x) 10 mm ² - 35 mm ² (1x)	
Terminal capacity (copper busbar)		Max. 12 mm x 5 mm Max. 16 mm x 5 mm	
Design verification as per IEC/EN 61439			
10.2.2 Corrosion resistance		Meets the product standard's requirements.	
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.	
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.	
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.	
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.	
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.	
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.	
10.2.7 Inscriptions		Meets the product standard's requirements.	
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.	
10.4 Clearances and creepage distances		Meets the product standard's requirements.	
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.	
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.	
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.	
10.8 Connections for external conductors		Is the panel builder's responsibility.	
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.	
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.	
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.	
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.	
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.	

10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Model			Other

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss13-27-37-04-24 [ACN957016])			
Suitable for number of poles			3
Model			Other