


## Load current switches, main switches, maintenance/repair switches

http://catalog.moeller.net

Moeller HPL0211-2007/2008

T, P **xCommand**

| Contact sequence<br>Front plate no.                                                                                    | Main conducting<br>paths | Auxiliary<br>contacts | Max.<br>motor<br>rating         | Rated uninter-<br>rupted<br>current | Design | Protection<br>type | Part no.<br>Article no.                                                                      | Price<br>see price<br>list                       | Std. pack |
|------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------|---------------------------------|-------------------------------------|--------|--------------------|----------------------------------------------------------------------------------------------|--------------------------------------------------|-----------|
| <br>FS 908                            | No. of<br>poles          |                       | AC-23A<br>400/415 V<br>50-60 Hz |                                     |        |                    |                                                                                              |                                                  |           |
|                                                                                                                        | I N/O                    | I N/O L N/C           | P kW                            | I <sub>u</sub> A                    |        |                    |                                                                                              |                                                  |           |
| <b>Main switches, maintenance switches</b>                                                                             |                          |                       |                                 |                                     |        |                    |                                                                                              |                                                  |           |
| According to IEC/EN 60204-1, VDE 0113 Part 1; with red rotary handle and yellow locking collar, lockable in 0 position |                          |                       |                                 |                                     |        |                    |                                                                                              |                                                  |           |
| As Emergency-Stop device                                                                                               |                          |                       |                                 |                                     |        |                    |                                                                                              |                                                  |           |
|                                       | 6                        | 1                     | 1                               | 30                                  | 100    | Surface mounting   | IP65<br>   | T5-4-15682/I5/SVB<br>207281                      | 1 off     |
|                                       | 6                        | 1                     | 1                               | 30                                  | 100    | Flush mounting     | Front IP65                                                                                   | T5-4-15682/EA/SVB<br>207413                      |           |
|                                       | 6                        | 1                     | 1                               | 30                                  | 100    | Rear mounting      | Front IP65                                                                                   | T5-4-15682/V/SVB<br>207415                       |           |
|                                       | 6                        | 1                     | 1                               | 55                                  | 160    | Rear mounting      | Front IP65                                                                                   | T6-160-6/V/SVB/HI11<br>200619                    |           |
|                                       | 6                        | 1                     | 1                               | 55                                  | 160    | Surface mounting   | IP65<br>   | T6-160-6/I45/SVB/HI11 <sup>1)</sup><br>201448    |           |
|                                       | 6                        | 1                     | 1                               | 132                                 | 315    | Rear mounting      | Front IP65                                                                                   | T8-3-8342/V/SVB/HI11 <sup>2)</sup><br>200620     |           |
|                                      | 6                        | 1                     | 1                               | 132                                 | 315    | Surface mounting   | IP65<br>  | T8-3-8342/I48/SVB/HI11 <sup>2)3)</sup><br>201450 |           |
| <b>Main switches, maintenance switches</b>                                                                             |                          |                       |                                 |                                     |        |                    |                                                                                              |                                                  |           |
| With black rotary handle and locking collar, lockable in the 0 position                                                |                          |                       |                                 |                                     |        |                    |                                                                                              |                                                  |           |
| Without Emergency-Stop function                                                                                        |                          |                       |                                 |                                     |        |                    |                                                                                              |                                                  |           |
|                                     | 1                        | 0                     | 0                               | 6.5                                 | 20     | Surface mounting   | IP65<br> | T0-1-8200/I1/SVB-SW<br>207146                    | 1 off     |
|                                     | 1                        | 0                     | 0                               | 6.5                                 | 20     | Flush mounting     | Front IP65                                                                                   | T0-1-8200/EA/SVB-SW<br>055483                    |           |
|                                     | 1                        | 0                     | 0                               | 13                                  | 32     | Surface mounting   | IP65<br> | T3-1-8200/I2/SVB-SW<br>207201                    |           |
|                                     | 2                        | 0                     | 0                               | 6.5                                 | 20     | Surface mounting   | IP65<br> | T0-1-102/I1/SVB-SW<br>207144                     |           |
|                                     | 2                        | 0                     | 0                               | 6.5                                 | 20     | Flush mounting     | Front IP65                                                                                   | T0-1-102/EA/SVB-SW<br>093451                     |           |
|                                     | 2                        | 0                     | 0                               | 6.5                                 | 20     | Rear mounting      | Front IP65                                                                                   | T0-1-102/V/SVB-SW<br>022330                      |           |
|                                     | 2                        | 0                     | 0                               | 13                                  | 32     | Surface mounting   | IP65<br> | T3-1-102/I2/SVB-SW<br>207199                     |           |
|                                     | 2                        | 0                     | 0                               | 13                                  | 32     | Flush mounting     | Front IP65                                                                                   | T3-1-102/EA/SVB-SW<br>016747                     |           |
|                                     | 3                        | 0                     | 0                               | 6.5                                 | 20     | Surface mounting   | IP65<br> | T0-2-1/I1/SVB-SW<br>207148                       |           |
|                                     | 3                        | 0                     | 0                               | 6.5                                 | 20     | Flush mounting     | Front IP65                                                                                   | T0-2-1/EA/SVB-SW<br>041246                       |           |
|                                     | 3                        | 0                     | 0                               | 6.5                                 | 20     | Rear mounting      | Front IP65                                                                                   | T0-2-1/V/SVB-SW<br>045992                        |           |
|                                     | 3                        | 0                     | 0                               | 13                                  | 25     | Surface mounting   | IP65<br> | P1-25/I2/SVB-SW<br>207294                        |           |
|                                     | 3                        | 0                     | 0                               | 13                                  | 25     | Surface mounting   | IP65<br> | P1-25/I2H/SVB-SW <sup>4)</sup><br>227861         |           |
|                                     | 3                        | 0                     | 0                               | 13                                  | 25     | Flush mounting     | Front IP65                                                                                   | P1-25/EA/SVB-SW<br>048365                        |           |
|                                     | 3                        | 0                     | 0                               | 13                                  | 25     | Rear mounting      | Front IP65                                                                                   | P1-25/V/SVB-SW<br>050738                         |           |

## Notes

<sup>1)</sup> Enclosures without flanges with K95/1N/BR<sup>2)</sup> with KS4-CI and K150/1/BR: Ingress protection IP64<sup>3)</sup> Rated uninterrupted current 315 A in enclosed version max. 275 A<sup>4)</sup> Enclosures with hard metric knock-outs