




Load current switches, main switches, maintenance/repair switches

http://catalog.moeller.net

Moeller HPL0211-2007/2008

T, P **xCommand**

Contact sequence Front plate no.	Main conduct- ing paths	Auxiliary contacts	Max. motor rating	Rated uninter- rupted current	Design	Protection type	Part no. Article no.	Price see price list	Std. pack
 FS 908	No. of poles		AC-23A 400/415 V 50-60 Hz						
	 N/O  N/O  N/C  P/C			I_u A					
Main switches, maintenance switches									
With black rotary handle and locking collar, lockable in the 0 position									
Without Emergency-Stop function									
	3 + N	1	1	13	25	Flush mounting	Front IP65	P1-25/EA/SVB-SW/N/HI11 050740	1 off
	3 + N	1	1	15	32	Flush mounting	Front IP65	P1-32/EA/SVB-SW/N/HI11 060232	
	3 + N	1	1	15	32	Rear mounting	Front IP65	P1-32/V/SVB-SW/N/HI11 064978	
	3 + N	1	1	37	63	Surface mounting	IP65	P3-63/I4/SVB-SW/N/HI11 207347	
	3 + N	1	1	37	63	Flush mounting	Front IP65	P3-63/EA/SVB-SW/N/HI11 069724	
	3 + N	1	1	37	63	Rear mounting	Front IP65	P3-63/V/SVB-SW/N/HI11 074470	
	3 + N	1	1	50	100	Surface mounting	IP65	P3-100/I5/SVB-SW/N/HI11 207377	
	3 + N	1	1	50	100	Flush mounting	Front IP65	P3-100/EA/SVB-SW/N/HI11 079216	
	3 + N	1	1	50	100	Rear mounting	Front IP65	P3-100/V/SVB-SW/N/HI11 083962	
	3 + N	1	1	6.5	20	Flush mounting	Front IP65	T0-3-8901/EA/SVB-SW 231933	
	3 + N	1	1	13	32	Surface mounting	IP65	T3-3-8901/I2/SVB-SW 218988	
	3 + N	1	1	22	63	Surface mounting	IP65	T5B-3-8901/I4/SVB-SW 207245	
	3 + N	1	1	22	63	Flush mounting	Front IP65	T5B-3-8901/EA/SVB-SW 207421	
	3 + N	1	1	30	100	Surface mounting	IP65	T5-3-8901/I5/SVB-SW 207278	
	6	1	1	6.5	20	Surface mounting	IP65	T0-4-15682/I1/SVB-SW 207162	
	6	1	1	6.5	20	Flush mounting	Front IP65	T0-4-15682/EA/SVB-SW 022265	
	6	1	1	6.5	20	Rear mounting	Front IP65	T0-4-15682/V/SVB-SW 027011	
	6	1	1	13	32	Surface mounting	IP65	T3-4-15682/I2/SVB-SW 207211	
	6	1	1	13	32	Flush mounting	Front IP65	T3-4-15682/EA/SVB-SW 057089	
	6	1	1	13	32	Rear mounting	Front IP65	T3-4-15682/V/SVB-SW 061835	
	6	1	1	22	63	Surface mounting	IP65	T5B-4-15682/I4/SVB-SW 207247	
	6	1	1	22	63	Flush mounting	Front IP65	T5B-4-15682/EA/SVB-SW 207426	
	6	1	1	22	63	Rear mounting	Front IP65	T5B-4-15682/V/SVB-SW 207428	
	6	1	1	30	100	Surface mounting	IP65	T5-4-15682/I5/SVB-SW 207282	
	6	1	1	30	100	Flush mounting	Front IP65	T5-4-15682/EA/SVB-SW 207414	
	6	1	1	30	100	Rear mounting	Front IP65	T5-4-15682/V/SVB-SW 207416	
	6	1	1	55	160	Surface mounting	IP65	T6-160-6/I45/SVB-SW/HI11 ¹⁾ 201447	
	6	1	1	55	160	Rear mounting	Front IP65	T6-160-6/V/SVB-SW/HI11 200127	
	6	1	1	132	315	Surface mounting	IP65	T8-3-8342/I48/SVB-SW/ HI11 ²⁾³⁾ 201449	
	6	1	1	132	315	Rear mounting	Front IP65	T8-3-8342/V/SVB-SW/HI11 ³⁾ 200128	

Notes

¹⁾ Enclosures without flanges with K95/1N/BR²⁾ with KS4-CI and K150/1/BR: IP64³⁾ Rated uninterrupted current 315 A in enclosed version max. 275 A