


Contact sequence	Front plate no.	Main conducting paths	Max. motor rating	Rated uninterrupted current	Design	Protection type	Part no. Article no.	Price see price list	Std. pack
		No. of poles	AC-23A						
			400/415 V 50-60 Hz						
		N/O	<i>P</i>	<i>I_u</i>					
		$\frac{1}{\sqrt{2}}$	kW	A					

Changeover switches

With black thumb-grip and grey front plate

With 0 (Off) position

Group switches, mains transfer switches



3	13	32	Surface mounting	IP65 totally insulated	T3-3-8212/I2 207183	
3	13	32	Flush mounting	Front IP65	T3-3-8212/E 068956	
3	13	32	Centre mounting	Front IP65	T3-3-8212/EZ 003080	
3	13	32	Rear mounting	Front IP65	T3-3-8212/Z 071329	
3	22	63	Surface mounting	IP65 totally insulated	T5B-3-8212/I4 207223	
3	22	63	Flush mounting	Front IP65	T5B-3-8212/E 092386	
3	22	63	Rear mounting	Front IP65	T5B-3-8212/Z 092383	
3	30	100	Flush mounting	Front IP65	T5-3-8212/E 096466	
3	30	100	Surface mounting	IP65 totally insulated	T5-3-8212/I5 207266	
3	30	100	Rear mounting	Front IP65	T5-3-8212/Z 096464	
3	45	125	Flush mounting	Front IP65	T6-3-8212/E/HI12 214781	
3	132	315	Flush mounting	Front IP65	T8-3-8212/E/HI12 214782	
4	6.5	20	Surface mounting	IP65 totally insulated	T0-4-8213/I1 207136	
4	6.5	20	Flush mounting	Front IP65	T0-4-8213/E 031726	
4	6.5	20	Distribution board mounting	Front IP30	T0-4-8213/IVS 081559	
4	6.5	20	Centre mounting	Front IP65	T0-4-8213/EZ 062575	
4	6.5	20	Rear mounting	Front IP65	T0-4-8213/Z 043592	
4	13	32	Surface mounting	IP65 totally insulated	T3-4-8213/I2 207191	
4	13	32	Flush mounting	Front IP65	T3-4-8213/E 076075	
4	13	32	Rear mounting	Front IP65	T3-4-8213/Z 078448	
4	22	63	Surface mounting	IP65 totally insulated	T5B-4-8213/I4 207230	
4	22	63	Flush mounting	Front IP65	T5B-4-8213/E 092112	
4	22	63	Rear mounting	Front IP65	T5B-4-8213/Z 092109	
4	30	100	Surface mounting	IP65 totally insulated	T5-4-8213/I5 207270	
4	30	100	Flush mounting	Front IP65	T5-4-8213/E 096014	
4	30	100	Rear mounting	Front IP65	T5-4-8213/Z 096012	

1 off

