

# Specifications



Photo is representative

## Eaton 107618

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 50A, box terminals, B2-AF50-BT-NA

### General specifications

|                             |                                                                                                                                                                                                                                                                                  |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic                                                                                                                                                                                                             |
| <b>CATALOG NUMBER</b>       | 107618                                                                                                                                                                                                                                                                           |
| <b>MODEL CODE</b>           | NZMB2-AF50-BT-NA                                                                                                                                                                                                                                                                 |
| <b>EAN</b>                  | 4015081072842                                                                                                                                                                                                                                                                    |
| <b>PRODUCT LENGTH/DEPTH</b> | 149 mm                                                                                                                                                                                                                                                                           |
| <b>PRODUCT HEIGHT</b>       | 195 mm                                                                                                                                                                                                                                                                           |
| <b>PRODUCT WIDTH</b>        | 105 mm                                                                                                                                                                                                                                                                           |
| <b>PRODUCT WEIGHT</b>       | 2.345 kg                                                                                                                                                                                                                                                                         |
| <b>COMPLIANCES</b>          | RoHS conform                                                                                                                                                                                                                                                                     |
| <b>CERTIFICATIONS</b>       | UL 489<br>Specially designed for North America<br>IEC/EN 60947<br>CE marking<br>CSA (Class No. 1432-01)<br>UL (File No. E31593)<br>CSA certified<br>CSA (File No. 22086)<br>UL/CSA<br>CSA-C22.2 No. 5-09<br>UL listed<br>IEC 60947-2<br>IEC<br>UL (Category Control Number DIVQ) |

## Product specifications

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>AMPERAGE RATING</b>                                                                  | 50 A                                                                                                                             |
| <b>VOLTAGE RATING</b>                                                                   | 690 V - 690 V                                                                                                                    |
| <b>CIRCUIT BREAKER FRAME TYPE</b>                                                       | NZM2                                                                                                                             |
| <b>FEATURES</b>                                                                         | Motor drive optional<br>Protection unit                                                                                          |
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                                                                                       |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to                                                                             |

## Resources

|                                  |                                                                                                                                                                                                                                                                                                                     |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                 | <a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a><br><a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a>                                                                                                                                                                    |
| <b>CATALOGUES</b>                | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-038.eps</a><br><a href="#">eaton-circuit-breaker-current-nzm-mccb-characteristic-curve-003.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-050.eps</a> |
| <b>CHARACTERISTIC CURVE</b>      | <a href="#">eaton-circuit-breaker-switch-nzm-mccb-dimensions-017.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-dimensions-019.eps</a><br><a href="#">eaton-circuit-breaker-switch-nzm-mccb-3d-drawing.eps</a>                                                                                               |
| <b>DRAWINGS</b>                  | <a href="#">ETN.107618.edz</a>                                                                                                                                                                                                                                                                                      |
| <b>ECAD MODEL</b>                | <a href="#">eaton-circuit-breakers-basic-device-nzm2-il01206006z.pdf</a>                                                                                                                                                                                                                                            |
| <b>INSTALLATION INSTRUCTIONS</b> | <a href="#">Introduction of the new digital circuit breaker NZM</a><br><a href="#">The new digital NZM Range</a>                                                                                                                                                                                                    |
| <b>INSTALLATION VIDEOS</b>       | <a href="#">DA-CS-nzm2_3p</a><br><a href="#">DA-CD-nzm2_3p</a>                                                                                                                                                                                                                                                      |
| <b>MCAD MODEL</b>                | <a href="#">eaton-nzm-technical-information-sheet</a>                                                                                                                                                                                                                                                               |
| <b>TECHNICAL DATA SHEETS</b>     |                                                                                                                                                                                                                                                                                                                     |

|                                                                 |                                                                                                      |
|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
|                                                                 | be evaluated.                                                                                        |
| <b>10.2.7 INSCRIPTIONS</b>                                      | Meets the product standard's requirements.                                                           |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                                           |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.                                   |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                                                               |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                                                               |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                                                               |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                                                               |
| <b>POLLUTION DEGREE</b>                                         | 3                                                                                                    |
| <b>MOUNTING METHOD</b>                                          | Fixed<br>Built-in device fixed built-in technique<br>DIN rail (top hat rail)<br>mounting optional    |
| <b>CLIMATIC PROOFING</b>                                        | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78                       |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>            | 17.03 W                                                                                              |
| <b>UTILIZATION CATEGORY</b>                                     | A (IEC/EN 60947-2)                                                                                   |
| <b>ISOLATION</b>                                                | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts) |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                      | 70 °C                                                                                                |
| <b>AMBIENT OPERATING</b>                                        | -25 °C                                                                                               |

|                                                                |                                                                                                                                                                 |
|----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>TEMPERATURE - MIN</b>                                       |                                                                                                                                                                 |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                       | 70 °C                                                                                                                                                           |
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                       | 40 °C                                                                                                                                                           |
| <b>LOW-VOLTAGE HBC FUSE - MAX</b>                              | 355 A gG/gL                                                                                                                                                     |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>     | 0                                                                                                                                                               |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 0                                                                                                                                                               |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 0                                                                                                                                                               |
| <b>PROTECTION AGAINST DIRECT CONTACT</b>                       | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110                                                                                                 |
| <b>DEGREE OF PROTECTION</b>                                    | IP20 (basic degree of protection, in the operating controls area)<br>IP20                                                                                       |
| <b>DIRECTION OF INCOMING SUPPLY</b>                            | As required                                                                                                                                                     |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>              | Frame clamp                                                                                                                                                     |
| <b>LIFESPAN, MECHANICAL</b>                                    | 20000 operations                                                                                                                                                |
| <b>OVERVOLTAGE CATEGORY</b>                                    | III                                                                                                                                                             |
| <b>RATED OPERATIONAL CURRENT</b>                               | 50 A (660-690 V AC-3, making and breaking capacity)<br>300 A (415 V AC-1, making and breaking capacity)<br>300 A (380/400 V AC-1, making and breaking capacity) |
| <b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>                   | IP40 (with insulating surround)<br>IP66 (with door coupling rotary handle)                                                                                      |
| <b>DEGREE OF PROTECTION (TERMINATIONS)</b>                     | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)                                                                                |
| <b>NUMBER OF POLES</b>                                         | Three-pole                                                                                                                                                      |
| <b>TERMINAL CAPACITY (COPPER STRIP)</b>                        | Min. 2 segments of 9 mm x 0.8 mm at box terminal                                                                                                                |

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                             | Min. 2 segments of 16 mm x 0.8 mm at rear-side connection (punched)<br>Max. 10 segments of 16 mm x 0.8 mm at rear-side connection (punched)<br>Max. 10 segments of 16 mm x 0.8 mm at box terminal                                                                                                                                                                                                                                                                                                                         |
| <b>LIFESPAN, ELECTRICAL</b> | 7500 operations at 400 V AC-1<br>6500 operations at 415 V AC-3                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>FUNCTIONS</b>            | Current limiting circuit breaker<br>System and cable protection                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>TYPE</b>                 | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>SPECIAL FEATURES</b>     | <ul style="list-style-type: none"> <li>• Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity <math>I_{cn}</math>)</li> <li>• Rated current = rated uninterrupted current: 50 A</li> <li>• Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate.</li> <li>• Fixed overload releases <math>I_r</math></li> </ul> |
| <b>APPLICATION</b>          | <ul style="list-style-type: none"> <li>• Branch circuits, feeder circuits</li> <li>• Use in unearthed supply systems at 440 V</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>SHOCK RESISTANCE</b>     | 20 g (half-sinusoidal shock)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

|                                                                      |                                                                                                                                                                                                                       |
|----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                      | 20 ms)                                                                                                                                                                                                                |
| <b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b>               | Front side                                                                                                                                                                                                            |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 50 A                                                                                                                                                                                                                  |
| <b>POWER LOSS</b>                                                    | 17 W                                                                                                                                                                                                                  |
| <b>RELEASE SYSTEM</b>                                                | Thermomagnetic release                                                                                                                                                                                                |
| <b>SHORT-CIRCUIT TOTAL BREAKTIME</b>                                 | < 10 ms                                                                                                                                                                                                               |
| <b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MAX</b>               | 500 A                                                                                                                                                                                                                 |
| <b>SHORT-CIRCUIT RELEASE NON-DELAYED SETTING - MIN</b>               | 300 A                                                                                                                                                                                                                 |
| <b>TERMINAL CAPACITY (CONTROL CABLE)</b>                             | 16 mm <sup>2</sup> - 18 mm <sup>2</sup> (2x)<br>14 mm <sup>2</sup> - 18 mm <sup>2</sup> (1x)                                                                                                                          |
| <b>TERMINAL CAPACITY (COPPER BUSBAR)</b>                             | Min. 16 mm x 5 mm direct at switch rear-side connection<br>Max. 20 mm x 5 mm direct at switch rear-side connection<br>M8 at rear-side screw connection                                                                |
| <b>TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)</b>              | 6 mm <sup>2</sup> - 11 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>16 mm <sup>2</sup> (1x) at tunnel terminal<br>6 mm <sup>2</sup> - 12 mm <sup>2</sup> (1x) at box terminal                        |
| <b>TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)</b>            | 16 mm <sup>2</sup> (1x) at tunnel terminal                                                                                                                                                                            |
| <b>TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)</b>           | 4 mm <sup>2</sup> - 3/0 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>4 mm <sup>2</sup> - 350 mm <sup>2</sup> (1x) at box terminal<br>4 mm <sup>2</sup> - 350 mm <sup>2</sup> (1x) at tunnel terminal |
| <b>HANDLE TYPE</b>                                                   | Rocker lever                                                                                                                                                                                                          |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MAX</b>                       | 0 A                                                                                                                                                                                                                   |
| <b>SHORT DELAY CURRENT SETTING (ISD) - MIN</b>                       | 0 A                                                                                                                                                                                                                   |
| <b>INSTANTANEOUS</b>                                                 | 500 A                                                                                                                                                                                                                 |

|                                                                                        |                   |
|----------------------------------------------------------------------------------------|-------------------|
| <b>CURRENT SETTING (II) - MAX</b>                                                      |                   |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>                                        | 300 A             |
| <b>NUMBER OF OPERATIONS PER HOUR - MAX</b>                                             | 120               |
| <b>OVERLOAD CURRENT SETTING (IR) - MAX</b>                                             | 50 A              |
| <b>OVERLOAD CURRENT SETTING (IR) - MIN</b>                                             | 50 A              |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ</b>     | 30 kA             |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ</b> | 25 kA             |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 440 V, 50/60 HZ</b>     | 18.5 kA           |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 400/415 V, 50/60 HZ</b>                  | 53 kA             |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 440 V, 50/60 HZ</b>                      | 53 kA             |
| <b>STANDARD TERMINALS</b>                                                              | Box terminal      |
| <b>RATED OPERATING VOLTAGE UE (UL) - MAX</b>                                           | 600Y/347 V, 480 V |
| <b>RATED SHORT-CIRCUIT MAKING CAPACITY ICM AT 240 V, 50/60 HZ</b>                      | 63 kA             |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS</b>                    | 6000 V            |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS</b>                         | 8000 V            |
| <b>RATED INSULATION VOLTAGE (UI)</b>                                                   | 690 V AC          |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

