

Specifications



Photo is representative

Eaton DILEM-01-G-C(24VDC)

Eaton XT IEC mini contactor, 9A, 24 Vdc, 1NC, 9A, 45 mm mini, 0.5, 1.5/ 2, 3, 5, 5 hp (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Non-reversing, XT IEC series, Full voltage non-reversing miniature contactor, 4 kW

General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	DILEM-01-G-C(24VDC)
EAN	4015082301675
PRODUCT LENGTH/DEPTH	1.8 in
PRODUCT HEIGHT	2.3 in
PRODUCT WIDTH	2 in
PRODUCT WEIGHT	0.48 lb
WARRANTY	1 year
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified EN 60947 IEC 60947

Product specifications

AMPERAGE RATING	9A
HP RATING - MAX	0.5, 1.5/ 2, 3, 5, 5 hp (1/3PH @120,240/208,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing miniature contactor
FRAME SIZE	45 mm - mini
COIL	24 Vdc
COIL VOLTAGE	24 Vdc
CONTACT CONFIGURATION	1 NC
CONTINUOUS AMPERE RATING	9 A
SERIES	XT IEC
OPERATION	Non-reversing
POWER CONSUMPTION	4 kW

Resources

	Contactors Explained
MULTIMEDIA	S1. E4. Ask the Experts - NEMA, IEC and DP contactors
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DILEM-01-G-C(24VDC)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

