

# Specifications



Photo is representative

Eaton

## DILM300/22(RAC500)

Eaton XT IEC large contactor, 300A, 480-500 Vac, 50-60 Hz, 300A, 50-60 Hz, Three-pole, Non-reversing, XT IEC series, Full voltage non-reversing large contactor, 160 kW

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC large contactor
<b>CATALOG NUMBER</b>	DILM300/22(RAC500)
<b>PRODUCT LENGTH/DEPTH</b>	208 mm
<b>PRODUCT HEIGHT</b>	189 mm
<b>PRODUCT WIDTH</b>	160 mm
<b>PRODUCT WEIGHT</b>	7.23 kg
<b>COMPLIANCES</b>	CE Marked RoHS Compliant
<b>CERTIFICATIONS</b>	IEC 60947 CSA Certified EN 60947 UL Listed

## Product specifications

AMPERAGE RATING	300 A
HP RATING - MAX	100, 125, 250, 300 (3PH @208,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing large contactor
VOLTAGE RATING	400 V
FREQUENCY RATING	50-60 Hz
CONNECTION	Screw connection
FRAME SIZE	160 mm
TERMINALS	Screw terminals
OPERATING TEMPERATURE - MAX	60 °C
OPERATING TEMPERATURE - MIN	-25 °C
COIL VOLTAGE	480-500 Vac, 50/60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	300 A
SERIES	XT IEC
NUMBER OF CONTACTS	2 NO 2 NC
OPERATION	Non-reversing
POWER CONSUMPTION	160 kW

## Resources

BROCHURES	<a href="#">C440 Electronic Overload Relay</a>
	<a href="#">Contactors Explained</a>
MULTIMEDIA	<a href="#">S1. E4. Ask the Experts - NEMA, IEC and DP contactors</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

