

# Specifications



## Eaton 208282

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/O, 1 NC, Side mounted, Screw terminals, DILM250 - DILH2600

### General specifications

|                                 |                                                                                                                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>             | Eaton Moeller® series<br>DILM auxiliary contact<br>module                                                                                                                                                     |
| <b>CATALOG NUMBER</b>           | 208282                                                                                                                                                                                                        |
| <b>MODEL CODE</b>               | DILM820-XHI11-SA                                                                                                                                                                                              |
| <b>EAN</b>                      | 4015082082826                                                                                                                                                                                                 |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 77 mm                                                                                                                                                                                                         |
| <b>PRODUCT HEIGHT</b>           | 77 mm                                                                                                                                                                                                         |
| <b>PRODUCT WIDTH</b>            | 15 mm                                                                                                                                                                                                         |
| <b>PRODUCT WEIGHT</b>           | 0.041 kg                                                                                                                                                                                                      |
| <b>CERTIFICATIONS</b>           | CSA<br>UL 508<br>CSA Class No.: 3211-04<br>IEC/EN 60947<br>UL Category Control No.:<br>NKCR<br>CSA File No.: 012528<br>UL File No.: E29184<br>CSA-C22.2 No. 14-05<br>CE<br>IEC/EN 60947-4-1<br>UL<br>VDE 0660 |
| <b>GLOBAL CATALOG</b>           | 208282                                                                                                                                                                                                        |

## Product specifications

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>TYPE</b>                                                                             | Side-mounting auxiliary contacts                                                                                                 |
| <b>FEATURES</b>                                                                         | Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)                            |
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                                                                                       |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to                                                                             |

## Resources

|                                   |                                                                                                                                                                                                                                                                                                              |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CATALOGS</b>                   | <a href="#">SmartWire-DT Catalog</a><br><a href="#">Product Range Catalog</a><br><a href="#">Switching and protecting motors</a><br><a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>                                                                                   |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">DA-DC-00004803.pdf</a><br><a href="#">DA-DC-00005052.pdf</a><br><a href="#">DA-DC-00004796.pdf</a><br><a href="#">DA-DC-00004670.pdf</a><br><a href="#">DA-DC-00004804.pdf</a><br><a href="#">DA-DC-00004669.pdf</a><br><a href="#">DA-DC-00005043.pdf</a><br><a href="#">DA-DC-00004798.pdf</a> |
| <b>DRAWINGS</b>                   | <a href="#">eaton-contactors-module-dilm-accessory-3d-drawing.eps</a>                                                                                                                                                                                                                                        |
| <b>ECAD MODEL</b>                 | <a href="#">ETN.DILM820-XHI11-SA</a>                                                                                                                                                                                                                                                                         |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">IL034095ZU</a> <a href="#">IL034037ZU</a>                                                                                                                                                                                                                                                        |
| <b>INSTALLATION VIDEOS</b>        | <a href="#">WIN-WIN with push-in technology</a>                                                                                                                                                                                                                                                              |
| <b>MCAD MODEL</b>                 | <a href="#">dil_m32_xhi11_s</a><br><a href="#">dil_m32_xhi11_s.stp</a>                                                                                                                                                                                                                                       |
| <b>WIRING DIAGRAMS</b>            | <a href="#">eaton-contactors-mounting-dilm-accessory-wiring-diagram-003.eps</a>                                                                                                                                                                                                                              |

|                                                                 |                                                                                |
|-----------------------------------------------------------------|--------------------------------------------------------------------------------|
|                                                                 | be evaluated.                                                                  |
| <b>10.2.7 INSCRIPTIONS</b>                                      | Meets the product standard's requirements.                                     |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                  | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                   | Meets the product standard's requirements.                                     |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                   | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated.             |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                                         |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                                         |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                                         |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                                         |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                                         |
| <b>ELECTRIC CONNECTION TYPE</b>                                 | Screw connection                                                               |
| <b>FITTED WITH:</b>                                             | Interlocked opposing contacts                                                  |
| <b>POLLUTION DEGREE</b>                                         | 3                                                                              |
| <b>CLIMATIC PROOFING</b>                                        | Damp heat, cyclic, to IEC 60068-2-30<br>Damp heat, constant, to IEC 60068-2-78 |
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                      | 60 °C                                                                          |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                      | -40 °C                                                                         |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>           | 40 °C                                                                          |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>           | -25 °C                                                                         |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                        | 80 °C                                                                          |

|                                                                |                                                                                                                                |
|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                       | -40 °C                                                                                                                         |
| <b>CONVENTIONAL THERMAL CURRENT ITH AT 60°C (3-POLE, OPEN)</b> | 10 A                                                                                                                           |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>      | 0.25 W                                                                                                                         |
| <b>HEAT DISSIPATION CAPACITY PDISS</b>                         | 0 W                                                                                                                            |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>       | 0.11 W                                                                                                                         |
| <b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>               | 0                                                                                                                              |
| <b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>           | 1                                                                                                                              |
| <b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>             | 1                                                                                                                              |
| <b>NUMBER OF SWITCHES (FAULT SIGNAL)</b>                       | 0                                                                                                                              |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>                  | 6000 V AC<br>6000 V                                                                                                            |
| <b>SCREWDRIVER SIZE</b>                                        | 0.8 x 5.5/1 x 6 mm,<br>Terminal screw, Standard screwdriver<br>2, Terminal screw, Control circuit cables, Pozidriv screwdriver |
| <b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)</b>            | 1 kA at 500 V                                                                                                                  |
| <b>MOUNTING METHOD</b>                                         | Side mounting                                                                                                                  |
| <b>CONNECTION</b>                                              | Screw terminals                                                                                                                |
| <b>OVERVOLTAGE CATEGORY</b>                                    | III                                                                                                                            |
| <b>CONTROL CIRCUIT RELIABILITY</b>                             | $\lambda < 5 \times 1/10^7$ (1 failure at 2,000,000 operations for $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)      |
| <b>DEGREE OF PROTECTION</b>                                    | IP20                                                                                                                           |
| <b>MODEL</b>                                                   | Top mounting                                                                                                                   |
| <b>LAMP HOLDER</b>                                             | None                                                                                                                           |
| <b>FUNCTIONS</b>                                               | For standard applications                                                                                                      |

|                                                             |                                                                                                                                                                                                                                                             |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SAFE ISOLATION</b>                                       | 440 V AC, Between auxiliary contacts, According to EN 61140<br>440 V AC, Between auxiliary contacts and main contacts, According to EN 61140<br>440 V AC, Between coil and auxiliary contacts, According to EN 61140                                        |
| <b>RATED OPERATIONAL CURRENT (IE)</b>                       | 3 A at 110 V, DC L/R $\leq$ 15 ms (with 1 contact in series)<br>1 A at 220 V, DC L/R $\leq$ 15 ms (with 1 contact in series)<br>6 A at 60 V, DC L/R $\leq$ 15 ms (with 1 contact in series)<br>10 A at 24 V, DC L/R $\leq$ 15 ms (with 1 contact in series) |
| <b>SCREW SIZE</b>                                           | M3.5, Terminal screw, Control circuit cables                                                                                                                                                                                                                |
| <b>LIFESPAN, ELECTRICAL</b>                                 | 1,300,000 Operations (at 230 V, AC-15, 3 A)                                                                                                                                                                                                                 |
| <b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b> | 1 A, 250 V DC, (UL/CSA)<br>15 A, 600 V AC, (UL/CSA)                                                                                                                                                                                                         |
| <b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>  | A600, AC operated (UL/CSA)<br>P300, DC operated (UL/CSA)                                                                                                                                                                                                    |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>   | 0 W                                                                                                                                                                                                                                                         |
| <b>PROTECTION</b>                                           | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)                                                                                                                                                        |
| <b>NUMBER OF POLES</b>                                      | Two-pole                                                                                                                                                                                                                                                    |
| <b>SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING</b>      | 16 A gG/gL, 500 V, Max. Fuse, Contacts                                                                                                                                                                                                                      |
| <b>SHORT-CIRCUIT PROTECTION RATING</b>                      | Max. 16 A gG/gL, Fuse, Without welding, Auxiliary contacts<br>FAZ-C4/1, Maximum overcurrent protective device, Short-circuit rating without welding, Short-circuit protection only,                                                                         |

| Contacts                                                             |                                                                      |
|----------------------------------------------------------------------|----------------------------------------------------------------------|
| <b>RATED INSULATION VOLTAGE (UI)</b>                                 | 690 V                                                                |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>  | 6 A                                                                  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>  | 4 A                                                                  |
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V</b>                | 1.5 A                                                                |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V</b>                | 0.8 A                                                                |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V</b>         | 0.3 A                                                                |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V</b>                 | 2 A                                                                  |
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V</b>                 | 1.5 A                                                                |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 6 A                                                                  |
| <b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>                    | 500 V                                                                |
| <b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>                     | 2 x (0.75 - 2.5) mm <sup>2</sup><br>1 x (0.75 - 2.5) mm <sup>2</sup> |
| <b>TERMINAL CAPACITY (SOLID)</b>                                     | 2 x (0.75 - 2.5) mm <sup>2</sup><br>1 x (0.75 - 2.5) mm <sup>2</sup> |
| <b>TIGHTENING TORQUE</b>                                             | 1.2 Nm, Screw terminals                                              |
| <b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>                        | 18 - 14                                                              |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

