

Specifications



Photo is representative

Eaton DILMF65(RAC120)

Eaton XT IEC contactor, 65A, 120 Vdc, 0NO-0NC, 65A, Frame F, 55 mm, 5, 15/ 20, 25, 50, 60 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing contactor, 30 kW

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	DILMF65(RAC120)
EAN	4015081042852
PRODUCT LENGTH/DEPTH	2.2 in
PRODUCT HEIGHT	4.5 in
PRODUCT WIDTH	5.2 in
PRODUCT WEIGHT	1.98 lb
WARRANTY	1 year
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC 60947 UL Listed CSA Certified EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A).

Product specifications

AMPERAGE RATING	65A
HP RATING - MAX	5, 15/ 20, 25, 50, 60 (1/3PH @120,240/208,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FRAME SIZE	55 mm
TERMINALS	Screw terminals
COIL	120 Vdc
COIL VOLTAGE	120 Vdc
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	65 A
SERIES	XT IEC
OPERATION	Non-reversing
POWER CONSUMPTION	30 kW

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - DILMF65\(RAC120\)](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

