

Specifications



Eaton 104467

Eaton Moeller® series DILMF Contactors for Semiconductor Industries acc. to SEMI F47, 380 V 400 V: 65 A, RAC 48: 42 - 48 V 50/60 Hz, Screw terminals

General specifications

| | |
|---------------------------------|--|
| PRODUCT NAME | Eaton Moeller® series DILMF contactor for semiconductor industries |
| CATALOG NUMBER | 104467 |
| EAN | 4015081042845 |
| PRODUCT LENGTH/DEPTH | 132.1 mm |
| PRODUCT HEIGHT | 115 mm |
| PRODUCT WIDTH | 55 mm |
| PRODUCT WEIGHT | 1.04 kg |
| CERTIFICATIONS | CSA File No.: 012528 IEC/EN 60947-4-1 CSA CSA-C22.2 No. 60947-4-1- 14 UL UL File No.: E29096 CE CSA Class No.: 2411-03, 3211-04 UL 60947-4-1 UL Category Control No.: NLDX |
| CATALOG NOTES | Also tested according to AC-3e. |
| MODEL CODE | DILMF65(RAC48) |

Features & Functions

| | |
|------------------------|-----------------------------|
| FITTED WITH: | Built-in suppressor circuit |
| NUMBER OF POLES | Three-pole |

Climatic environmental conditions

| | |
|--|--------|
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
|--|--------|

| | |
|--|-------|
| AMBIENT OPERATING TEMPERATURE - MAX | 60 °C |
|--|-------|

| | |
|---|--------|
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN | -25 °C |
|---|--------|

| | |
|---|-------|
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX | 40 °C |
|---|-------|

| | |
|--|--------|
| AMBIENT STORAGE TEMPERATURE - MIN | -40 °C |
|--|--------|

| | |
|--|-------|
| AMBIENT STORAGE TEMPERATURE - MAX | 80 °C |
|--|-------|

General

| | |
|--------------------|--|
| APPLICATION | Contactors for Semiconductor Industries acc. to SEMI F47 |
|--------------------|--|

| | |
|-----------------------------|-----|
| OVERVOLTAGE CATEGORY | III |
|-----------------------------|-----|

| | |
|-------------------------|---|
| POLLUTION DEGREE | 3 |
|-------------------------|---|

| | |
|-------------------------|------------|
| PRODUCT CATEGORY | Contactors |
|-------------------------|------------|

| | |
|----------------------------|---------|
| RESISTANCE PER POLE | 1.86 mΩ |
|----------------------------|---------|

| | |
|---------------------|---|
| SUITABLE FOR | SEMI F47, Magnet systems Also motors with efficiency class IE3 |
|---------------------|---|

| | |
|-----------------------------|---|
| UTILIZATION CATEGORY | AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running |
|-----------------------------|---|

| | |
|---------------------|----|
| VOLTAGE TYPE | AC |
|---------------------|----|

Electro Magnetic Compatibility

| | |
|-----------------------------|-------------------------|
| EMITTED INTERFERENCE | According to EN 60947-1 |
|-----------------------------|-------------------------|

| | |
|------------------------------|-------------------------|
| INTERFERENCE IMMUNITY | According to EN 60947-1 |
|------------------------------|-------------------------|

Electrical Rating

**RATED OPERATIONAL
CURRENT (IE) AT AC-1,
380 V, 400 V, 415 V** 85 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
220 V, 230 V, 240 V** 65 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
380 V, 400 V, 415 V** 65 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
440 V** 65 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
500 V** 65 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
660 V, 690 V** 37 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-4,
220 V, 230 V, 240 V** 25 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-4,
400 V** 25 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-4,
500 V** 25 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-4,
660 V, 690 V** 20 A

**RATED INSULATION
VOLTAGE (UI)** 690 V

**RATED OPERATIONAL
CURRENT (IE) AT AC-1,
380 V, 400 V, 415 V** 85 A

**RATED OPERATIONAL
POWER AT AC-3, 240 V, 50
HZ** 22 kW

**RATED OPERATIONAL
POWER AT AC-3, 380/400
V, 50 HZ** 30 kW

**RATED OPERATIONAL
POWER AT AC-3, 415 V, 50
HZ** 39 kW

**RATED OPERATIONAL
POWER AT AC-4, 220/230
V, 50 HZ** 7 kW

RATED OPERATIONAL 7.5 kW

Short-circuit rating

**SHORT-CIRCUIT CURRENT
RATING (BASIC RATING)** 250 A, max. Fuse, SCCR
(UL/CSA)
10 kA, SCCR (UL/CSA)
250 A, max. CB, SCCR
(UL/CSA)

**SHORT-CIRCUIT CURRENT
RATING (HIGH FAULT AT
480 V)** 100 A, max. CB, SCCR
(UL/CSA)
250/150 A, Class J, max.
Fuse, SCCR (UL/CSA)
65 kA, CB, SCCR (UL/CSA)
30/100 kA, Fuse, SCCR
(UL/CSA)

**SHORT-CIRCUIT CURRENT
RATING (HIGH FAULT AT
600 V)** 30 kA, CB, SCCR (UL/CSA)
30/100 kA, Fuse, SCCR
(UL/CSA)
250 A, max. CB, SCCR
(UL/CSA)
250/150 A, Class J, max.
Fuse, SCCR (UL/CSA)

POWER AT AC-4, 240 V, 50 HZ

| | |
|--|-------|
| RATED OPERATIONAL POWER AT AC-4, 415 V, 50 HZ | 13 kW |
|--|-------|

| | |
|--|-------|
| RATED OPERATIONAL POWER AT AC-4, 440 V, 50 HZ | 14 kW |
|--|-------|

| | |
|--|-------|
| RATED OPERATIONAL POWER AT AC-4, 500 V, 50 HZ | 16 kW |
|--|-------|

| | |
|--|-------|
| RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ | 17 kW |
|--|-------|

Conventional thermal current

| | |
|--|-------|
| CONVENTIONAL THERMAL CURRENT ITH (1-POLE, ENCLOSED) | 180 A |
|--|-------|

| | |
|--|------|
| CONVENTIONAL THERMAL CURRENT ITH (3-POLE, ENCLOSED) | 72 A |
|--|------|

| | |
|---|-------|
| CONVENTIONAL THERMAL CURRENT ITH OF MAIN CONTACTS (1-POLE, OPEN) | 200 A |
|---|-------|

Switching time

| | |
|---|-------|
| SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX | 50 ms |
|---|-------|

| | |
|---|-------|
| SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX | 45 ms |
|---|-------|

Switching capacity

| | |
|--|-------------------------------------|
| SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE) | 88 A, Maximum motor rating (UL/CSA) |
|--|-------------------------------------|

Magnet system

| | |
|-------------------------|--|
| DROP-OUT VOLTAGE | AC operated: 0.5 - 0.2 x UC, AC operated |
|-------------------------|--|

| | |
|--------------------|-------|
| DUTY FACTOR | 100 % |
|--------------------|-------|

| | |
|------------------------|----------------------|
| PICK-UP VOLTAGE | 0.8 - 1.15 V AC x Uc |
|------------------------|----------------------|

| | |
|--|---|
| POWER CONSUMPTION, PICK-UP, 50 HZ | 45 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz |
|--|---|

| | |
|--|---|
| POWER CONSUMPTION, SEALING, 50 HZ | 1.3 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz 1.5 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz |
|--|---|

| | |
|---|------|
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN | 42 V |
|---|------|

| | |
|---|------|
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX | 48 V |
|---|------|

| | |
|---|------|
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN | 42 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX | 48 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN | 0 V |
| RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX | 0 V |

| Motor Rating | |
|--|-------|
| ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE | 5 HP |
| ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE | 20 HP |
| ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE | 15 HP |
| ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE | 25 HP |
| ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE | 50 HP |
| ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE | 60 HP |

| Contacts | |
|--|---|
| NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) | 0 |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) | 0 |

| Communication | |
|-------------------|-----------------|
| CONNECTION | Screw terminals |

| Special purpose ratings | |
|---|---|
| SPECIAL PURPOSE RATING OF BALLAST ELECTRICAL DISCHARGE LAMPS | 88 A (480V 60Hz 3phase, 277V 60Hz 1phase) 88 A (600V 60Hz 3phase, 347V 60Hz 1phase) |
| SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING | 390 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 65 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) |
| SPECIAL PURPOSE RATING OF ELEVATOR CONTROL | 30 HP, 480 V 60 Hz 3-ph, (UL/CSA) 15 HP, 240 V 60 Hz 3-ph, (UL/CSA) |

| | |
|--|--|
| | 42 A, 240 V 60 Hz 3-ph, (UL/CSA) 41 A, 600 V 60 Hz 3-ph, (UL/CSA) 10 HP, 200 V 60 Hz 3-ph, (UL/CSA) 40 HP, 600 V 60 Hz 3-ph, (UL/CSA) 32.2 A, 200 V 60 Hz 3-ph, (UL/CSA) 40 A, 480 V 60 Hz 3-ph, (UL/CSA) |
| SPECIAL PURPOSE RATING OF RESISTANCE AIR HEATING | 88 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 88 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) |
| SPECIAL PURPOSE RATING OF TUNGSTEN INCANDESCENT LAMPS | 88 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 88 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) |

Design verification

| | |
|---|--|
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID | 17.1 W |
| HEAT DISSIPATION CAPACITY PDISS | 0 W |
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 65 A |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR | Is the panel builder's |

Resources

| | |
|-----------------------------------|--|
| | eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf |
| CATALOGUES | Product Range Catalog Switching and protecting motors SmartWire-DT Catalog |
| CHARACTERISTIC CURVE | eaton-contactors-short-time-loading-dilm-characteristic-curve.eps eaton-contactors-component-dilm-characteristic-curve-003.eps |
| DECLARATIONS OF CONFORMITY | DA-DC-00004782.pdf DA-DC-00004817.pdf |
| DRAWINGS | eaton-contactors-dilm-dimensions-002.eps eaton-contactors-dilm-dimensions-012.eps eaton-contactors-mounting-dilm-dimensions.eps eaton-contactors-dilm-3d-drawing-011.eps eaton-general-ie-ready-dilm-contactor-standards.eps |
| ECAD MODEL | ETN.104467.edz |
| INSTALLATION INSTRUCTIONS | IL03407033Z |
| INSTALLATION VIDEOS | WIN-WIN with push-in technology |
| MCAD MODEL | DA-CS-dil m40 72 DA-CD-dil m40 72 |
| PEP ECO-PASSPORT | eaton-contactor-for-semiconductor-industries-declaration-of-conformity-eu250769en.pdf |
| SYSTEM OVERVIEW | eaton-contactors-circuit-breaker-dilmf-explosion-drawing.eps |

| | |
|---|--|
| EXTERNAL CONDUCTORS | responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

WIRING DIAGRAMS

[eaton-contactors-mounting-dilmf-explosion-drawing.eps](#)

[eaton-contactors-contact-dilm-wiring-diagram-003.eps](#)



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

