

Specifications



Photo is representative



Eaton NZMH2-A32

Eaton Series NZM complete molded case circuit breaker, NZM2-frame, NZMH2, adj. thermal, adj. magnetic trip, Three-pole, 32A, 690 Vac, 750 Vdc, 85-150 kAIC, Distribution circuit protection, 25-32A, 350-350A delayed, Front screw, 25-32A

General specifications

PRODUCT NAME	Eaton Series NZM complete molded case circuit breaker
CATALOG NUMBER	NZMH2-A32
EAN	4015082812836
PRODUCT LENGTH/DEPTH	4.05 in
PRODUCT HEIGHT	7.24 in
PRODUCT WIDTH	4.13 in
PRODUCT WEIGHT	4.1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	UL Listed



Powering Business Worldwide

Product specifications

AMPERAGE RATING	32 A
VOLTAGE RATING	690 Vac, 750 Vdc
TRIP TYPE	Adjustable thermal, adjustable magnetic
CIRCUIT BREAKER TYPE	NZMH2
FRAME	NZM2
CLASS	Distribution circuit protection
ACCESSORIES	Rocker lever, motor drive
ADJUSTMENT RANGE SHORT-CIRCUIT RELEASE	350-350A delayed
SETTING RANGE OL PROTECTOR	25-32A
SHORT-CIRCUIT BREAKING CAPACITY	150 kAIC
INTERRUPT RATING	85-150 kAIC
CONNECTION	Front screw
OVERLOAD RANGE	25-32A
NUMBER OF POLES	Three-pole

Resources

SPECIFICATIONS AND DATASHEETS [Eaton Specification Sheet - NZMH2-A32](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

