

Specifications



Photo is representative



Eaton NZMH2-A40-BT-NA

Eaton Series NZM complete molded case circuit breaker, NZM2-frame, NZMH2, Adj. thermal, adj. magnetic trip, Three-pole, 40A, 690 Vac, 750 Vdc, 85-150 kAIC, Box, Distribution circuit protect., 32-40A, Front frame clamp, 32-40A

General specifications

PRODUCT NAME	Eaton Series NZM complete molded case circuit breaker
CATALOG NUMBER	NZMH2-A40-BT-NA
EAN	4015081074471
PRODUCT LENGTH/DEPTH	4.05 in
PRODUCT HEIGHT	7.24 in
PRODUCT WIDTH	4.13 in
PRODUCT WEIGHT	4.1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed

Product specifications

AMPERAGE RATING	40 A
VOLTAGE RATING	690 Vac, 750 Vdc
TRIP TYPE	Adjustable thermal, adjustable magnetic
CIRCUIT BREAKER TYPE	NZMH2
TERMINALS	Box
FRAME	NZM2
CLASS	Distribution circuit protection
ACCESSORIES	Rocker lever, motor drive
ADJUSTMENT RANGE SHORT-CIRCUIT RELEASE	320-400A delayed
SETTING RANGE OL PROTECTOR	32-40A
SHORT-CIRCUIT BREAKING CAPACITY	150 kAIC
INTERRUPT RATING	85-150 kAIC
CONNECTION	Front frame clamp
OVERLOAD RANGE	32-40A
NUMBER OF POLES	Three-pole

Resources

APPLICATION NOTES	Power Xpert Protection Manager x64
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - NZMH2-A40-BT-NA
WHITE PAPERS	Intelligent power starts with accurate, actionable data

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

