Specifications



Photo is representative





Eaton NZMH2-A40

Eaton Series NZM complete molded case circuit breaker, NZM2-frame, NZMH2, Adj. thermal, Adj. magnetic trip, Three-pole, 40A, 750 Vdc, Dist. circuit protection, Rocker lever, motor drive, 32-40A, 320-400A delayed, 32-40A

General specifications		
PRODUCT NAME	Eaton Series NZM complete molded case circuit breaker	
CATALOG NUMBER	NZMH2-A40	
EAN	4015082590956	
PRODUCT LENGTH/DEPTH	4.05 in	
PRODUCT HEIGHT	7.24 in	
PRODUCT WIDTH	4.13 in	
PRODUCT WEIGHT	4.1 lb	
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
CERTIFICATIONS	UL Listed	



Product specifications		
AMPERAGE RATING	40 A	
VOLTAGE RATING	690 Vac, 750 Vdc	
TRIP TYPE	Adjustable thermal, adjustable magnetic	
CIRCUIT BREAKER TYPE	NZMH2	
FRAME	NZM2	
CLASS	Distribution circuit protection	
ACCESSORIES	Rocker lever, motor drive	
ADJUSTMENT RANGE SHORT-CIRCUIT RELEASE	320-400A delayed	
SETTING RANGE OL PROTECTOR	32-40A	
SHORT-CIRCUIT BREAKING CAPACITY	150 kAIC	
INTERRUPT RATING	85-150 kAIC	
CONNECTION	Front screw	
OVERLOAD RANGE	32-40A	
NUMBER OF POLES	Three-pole	

Resources	
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet -</u> <u>NZMH2-A40</u>
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









