

Specifications



Eaton XTOM004AC1

Eaton XT IEC control relay, XT IEC Miniature Overload Relay, 2.4-4A overload range, 45 mm - mini Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, 10A trip type

General specifications

PRODUCT NAME	Eaton XT IEC control relay
---------------------	----------------------------

CATALOG NUMBER	XTOM004AC1
-----------------------	------------

EAN	4015080145189
------------	---------------

PRODUCT LENGTH/DEPTH	3 in
-----------------------------	------

PRODUCT HEIGHT	2 in
-----------------------	------

PRODUCT WIDTH	3 in
----------------------	------

PRODUCT WEIGHT	0.7 lb
-----------------------	--------

COMPLIANCES	RoHS Compliant ATEX Compliant CE Marked
--------------------	-----------------------------------------------

CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
-----------------------	-----------------------------------------------------

CATALOG NOTES	Observe the maximum permissible fuse of the contactor with direct device mounting. Clearance of at least 5 mm is required between the overload relays when fitted directly to contactor.
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Powering Business Worldwide

Product specifications

OVERLOAD RANGE	2.4-4A
TYPE	Control relay
FRAME SIZE	45 mm - mini
CONTACT CONFIGURATION	1 NO, 1 NC
MOUNTING METHOD	Direct
TRIP TYPE	10 A

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOM004AC1

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

