

Specifications



Photo is representative



Eaton FAZ-B50/1-SP

Eaton FAZ supplementary protector,UL 1077 Industrial miniature circuit breaker-supplementary protector,Single package,Low levels of inrush current are expected,50A,15 kAIC,Single-pole,240/415 V,3-5X/n,Q38,50-60 Hz,Standard terminals,B Curve

General specifications

PRODUCT NAME	Eaton FAZ supplementary protector
CATALOG NUMBER	FAZ-B50/1-SP
EAN	4015081637515
PRODUCT LENGTH/DEPTH	0.69 in
PRODUCT HEIGHT	1 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	0.3 lb
WARRANTY	1 year
CERTIFICATIONS	IEC 60947-2 CSA Std. C22.2 No.235 UL 1077
CATALOG NOTES	For applications that require protection due to potential wiring damage at low fault conditions. Single packaging of single-pole curves for select amperages only.

Physical Attributes

NUMBER OF POLES	Single-pole
TERMINALS	Standard
TYPE	UL 1077 Industrial miniature circuit breaker - supplementary protector

Miscellaneous

APPLICATION	Suitable for applications where low levels of inrush current are expected
QUANTITY	38
SPECIAL FEATURES	Single package

Performance Ratings

AMPERAGE RATING	50 A
CIRCUIT PROTECTION	B curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	15 kAIC
TRIP TYPE	T17
VOLTAGE RATING	240/415V

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-B50/1-SP

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

