

Specifications



Eaton FAZ-C40/2

Eaton FAZ supplementary protector,UL 1077 Industrial miniature circuit breaker - supplementary protector,Medium levels of inrush current are expected,40 A,15 kAIC,Two-pole,5-10X /n,50-60 Hz,Standard terminals,C Curve

Photo is representative



General specifications

PRODUCT NAME	Eaton FAZ supplementary protector
CATALOG NUMBER	FAZ-C40/2
EAN	4015082787646
PRODUCT LENGTH/DEPTH	1.38 in
PRODUCT HEIGHT	1.38 in
PRODUCT WIDTH	1.5 in
PRODUCT WEIGHT	0.53 lb
WARRANTY	1 year
CERTIFICATIONS	UL 1077 IEC 60947-2 CSA Std. C22.2 No.235
CATALOG NOTES	Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices.

Physical Attributes

NUMBER OF POLES	Two-pole
TERMINALS	Standard
TYPE	UL 1077 Industrial miniature circuit breaker - supplementary protector

Miscellaneous

APPLICATION	Suitable for applications where medium levels of inrush current are expected
-------------	--

Performance Ratings

AMPERAGE RATING	40 A
CIRCUIT PROTECTION	C curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	15 kAIC
TRIP TYPE	5-10X /n

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-C40/2

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

