Specifications



Photo is representative





Eaton NZM2/3-XUHIV2024AC

Eaton molded case circuit breaker accessory undervoltage release, Undervoltage release, Contacts 3.23 and 3.24 with separate 3m connection cables., 24 V, Screw, NZM2 and NZM3, Frame J-K, Series NZM, 2NO, 24 V, 50/60 Hz

General specifications		
PRODUCT NAME	Eaton molded case circuit breaker accessory undervoltage release	
CATALOG NUMBER	NZM2/3-XUHIV2024AC	
EAN	4015082596408	
PRODUCT LENGTH/DEPTH	1.378 in	
PRODUCT HEIGHT	1.378 in	
PRODUCT WIDTH	1.378 in	
PRODUCT WEIGHT	0.295 lb	
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
COMPLIANCES	Contact Manufacturer	
GLOBAL CATALOG	NZM2/3-XUHIV2024AC	



Product specification	S
USED WITH	NZM2 and NZM3
VOLTAGE RATING	24 V
FRAME SIZE	Frame J-K
SERIES	Series NZM
FREQUENCY RATING	50/60 Hz
CONTACT CONFIGURATION	2 NO
RATED CONTROL SUPPLY VOLTAGE	24 V
CONNECTION	Screw
ТҮРЕ	Undervoltage release
APPLICATION	Contacts 3.23 and 3.24 with separate 3m connection cables.

Resources	
CATALOGS	Circuit Protection, Molded Case Circuit Breakers, Volume 4, Tab 2
MULTIMEDIA	Flex shaft handle installation tutorial
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - NZM2/3-XUHIV2024AC

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









