

Specifications



Eaton 266633

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, handle red, size 2

General specifications

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	266633
MODEL CODE	NZM2-XHBR
EAN	4015082666330
PRODUCT LENGTH/DEPTH	190 mm
PRODUCT HEIGHT	110 mm
PRODUCT WIDTH	110 mm
PRODUCT WEIGHT	0.948 kg
COMPLIANCES	IEC UL/CSA RoHS conform
CERTIFICATIONS	UL489 UL (File No. E140305) IEC60947 CSA (Class No. 1437-01) CSA (File No. 22086) UL (Category Control Number DIHS) CE marking CSA certified UL listed CSA-C22.2 No. 5-09
GLOBAL CATALOG	266633



Powering Business Worldwide

Product specifications

USED WITH	NZM2(-4) N(S)2(-4) PN2(-4)
FEATURES	With red door coupling rotary handle for use of switch as emergency switching off device to IEC/EN 60204-1, VDE 0113 part 1 Lockable
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGS	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-008.eps eaton-circuit-breaker-switch-nzm-mccb-dimensions.eps eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-005.eps
INSTALLATION INSTRUCTIONS	eaton-door-coupling-rotary-handle-nzm1-2-xt-il01203005z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	DA-CD-nzm2_xhb DA-CS-nzm2_xhb
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

	be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Red
FITTED WITH:	<p>Door coupling rotary handle with rotary drive NZM...-XV4 extension shaft</p> <p>Black and yellow lightning symbol External warning plate/marketing plate in German/English Extension shaft Padlock</p>
FRAME	NZM2
SUITABLE FOR	<p>Switch disconnecter Power circuit breaker Emergency stop</p>
COVER/DOOR TYPE	<p>Door interlock can only be switched ON when the door is closed Door interlock not</p>

	<p>defeated in the locked OFF position.</p> <p>Door interlock can be modified such that it can be defeated from the outside using a screwdriver</p> <p>After the door interlock is activated, must not be opened while on ON or TRIP. Must only be opened on OFF</p> <p>Door interlock on OFF with max. 3 padlocks</p>
--	--

LOCKING FACILITY	<p>Lockable on the 0 position on the handle using up to 3 padlocks</p> <p>With door interlock</p> <p>Lockable on the switch in the 0 position</p>
-------------------------	---

TYPE	<ul style="list-style-type: none"> • Accessory • Main switch assembly kit
-------------	---

SPECIAL FEATURES	<ul style="list-style-type: none"> • External warning plate/designation label can be clipped on. • For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. • Kit for use as a main switch
-------------------------	--

DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	<p>IP66</p> <p>4X. 12</p>
---	---------------------------

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.