Specifications



Photo is representative





Eaton NZMN2-A125-NA

Eaton Series NZM complete molded case circuit breaker, NZM2-frame, NZMN2, Thermal-magnetic trip, 750-1250A delayed trip rating, Three-pole, 125A, 690 Vac, 750 Vdc, 50 kAIC, Distribution circuit protection, 100-125A, Front screw, 100-125A

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton Series NZM complete molded case circuit breaker |
| CATALOG NUMBER | NZMN2-A125-NA |
| EAN | 4015082692254 |
| PRODUCT LENGTH/DEPTH | 5.9 in |
| PRODUCT HEIGHT | 7.7 in |
| PRODUCT WIDTH | 4.1 in |
| PRODUCT WEIGHT | 4.1 lb |
| WARRANTY | Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| COMPLIANCES | Contact Manufacturer |



| Product specifications | | |
|------------------------------------|---------------------------------|--|
| AMPERAGE RATING | 125 A | |
| VOLTAGE RATING | 690 Vac, 750 Vdc | |
| TRIP TYPE | T268 | |
| CIRCUIT BREAKER TYPE | NZMN2 | |
| FRAME | NZM2 | |
| CLASS | Distribution circuit protection | |
| ACCESSORIES | Rocker lever, motor drive | |
| SETTING RANGE OL PROTECTOR | 100-125A | |
| SHORT-CIRCUIT BREAKING CAPACITY | 50 kAIC | |
| INTERRUPT RATING | 50 kAIC | |
| CONNECTION | Front screw | |
| OVERLOAD RANGE | 100-125A | |
| NUMBER OF POLES | Three-pole | |
| TRIP RATING | 750-1250 A delayed | |

| Resources | |
|--------------------|-----------------------------|
| SPECIFICATIONS AND | Eaton Specification Sheet - |
| DATASHEETS | NZMN2-A125-NA |

| PROJECT NAME: |
|-----------------|
| PROJECT NUMBER: |
| PREPARED BY: |
| DATE: |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









