

Specifications



Photo is representative



Eaton NZMN2-AF25-NA

Eaton Series NZM complete molded case circuit breaker, NZM2-frame, NZMN2, Thermal-magnetic trip, Three-pole, 25A, 690 Vac, 750 Vdc, 50 kAIC, Distribution circuit protection, 25-25A, 350-350A delayed, Front screw, 25-25A

General specifications

PRODUCT NAME	Eaton Series NZM complete molded case circuit breaker
CATALOG NUMBER	NZMN2-AF25-NA
EAN	4015082691721
PRODUCT LENGTH/DEPTH	4.05 in
PRODUCT HEIGHT	7.24 in
PRODUCT WIDTH	4.13 in
PRODUCT WEIGHT	4.1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	Contact Manufacturer
CERTIFICATIONS	UL Listed

Product specifications

AMPERAGE RATING	25 A
VOLTAGE RATING	690 Vac, 750 Vdc
TRIP TYPE	T268
CIRCUIT BREAKER TYPE	NZMN2
FRAME	NZM2
CLASS	Distribution circuit protection
ACCESSORIES	Rocker lever, motor drive
ADJUSTMENT RANGE SHORT-CIRCUIT RELEASE	350-350A delayed
SETTING RANGE OL PROTECTOR	25-25A
SHORT-CIRCUIT BREAKING CAPACITY	50 kAIC
INTERRUPT RATING	50 kAIC
CONNECTION	Front screw
OVERLOAD RANGE	25-25A
NUMBER OF POLES	Three-pole

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - NZMN2-AF25-NA](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

