# Specifications



#### Photo is representative





# Eaton NZMN2-VE160-BT-NA

Eaton Series NZM complete molded case circuit breaker, NZM2-frame, NZMN2, Thermal-magnetic trip, 160-1600A delayed, 1920-1920A delayed, Three-pole, 160A, 690 Vac, 750 Vdc, 50 kAIC, Box, Selective and gen. protect., Front frame clamp

| General specifications  |   |
|-------------------------|---|
| PRODUCT NAME            | Eaton Series NZM<br>complete molded case<br>circuit breaker   |
| CATALOG NUMBER          | NZMN2-VE160-BT-NA   |
| EAN                     | 4015081074945   |
| PRODUCT<br>LENGTH/DEPTH | 5.9 in  |
| PRODUCT HEIGHT          | 7.7 in  |
| PRODUCT WIDTH           | 4.1 in  |
| PRODUCT WEIGHT          | 4.1 lb  |
| WARRANTY                | Eaton Selling Policy 25-<br>000, one (1) year from the<br>date of installation of the<br>Product or eighteen (18)<br>months from the date of<br>shipment of the Product,<br>whichever occurs first. |
| COMPLIANCES             | Contact Manufacturer  |



## **Product specifications**

| r rodaet speemedtion            |   |
|---------------------------------|---|
| AMPERAGE RATING                 | 160 A                                       |
| VOLTAGE RATING                  | 690 Vac, 750 Vdc                            |
| TRIP TYPE                       | T268  |
| CIRCUIT BREAKER TYPE            | NZMN2                                       |
| TERMINALS                       | Вох   |
| FRAME                           | NZM2  |
| CLASS                           | Selective and generator protection          |
| ACCESSORIES                     | Rocker lever, motor drive                   |
| SETTING RANGE OL<br>PROTECTOR   | 80-160A                                     |
| SHORT-CIRCUIT BREAKING CAPACITY | 50 kAIC                                     |
| INTERRUPT RATING                | 50 kAIC                                     |
| CONNECTION                      | Front frame clamp                           |
| OVERLOAD RANGE                  | 80-160A                                     |
| NUMBER OF POLES                 | Three-pole                                  |
| TRIP RATING                     | 160-1600 A delayed, 1920-<br>1920 A delayed |

| PROJECT | NAME:   |
|---------|---------|
| PROIFCT | NUMBER: |

**PREPARED BY:** 

DATE:



#### **Eaton Corporation plc**

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

### Resources

Follow us on social media to get the latest product and support information.









