

Specifications



Photo is representative

Eaton XTCE185H22W

Eaton XT IEC contactor, 185A, 42 Vac, 50 Hz, 48 Vac, 60 Hz, 2NO-2NC, 185A, Frame H, 140 mm, 50-60 Hz, 50, 75, 150, 200 hp (3PH @200, 240, 480, 600 V), Three-pole, Non-reversing, , Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE185H22W
EAN	4015081363131
PRODUCT LENGTH/DEPTH	10.25 in
PRODUCT HEIGHT	10 in
PRODUCT WIDTH	7.5 in
PRODUCT WEIGHT	8.85 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947

Product specifications

AMPERAGE RATING	185A
HP RATING - MAX	50, 75, 150, 200 hp (3PH @200,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	140 mm
TERMINALS	Screw terminals
COIL VOLTAGE	42-48 Vac, 50/60 Hz
CONTACT CONFIGURATION	2 NO, 2 NC
CONTINUOUS AMPERE RATING	185 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS

[Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTCE185H22W](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

