


					Moeller HPL0211-2007/2008		http://catalog.moeller.net	
					Basic switching capacity 25 kA at 415 V 50/60 Hz		Normal switching capacity 50 kA at 415 V 50/60 Hz	
Rated current = rated uninterrupted current		Setting range Short-circuit releases	Motor rating AC-3 at 400 V 50/60 Hz	Rated operational current AC-3 at 400 V 50/60 Hz	Part no. Article no.	Price see price list	Part no. Article no.	Price see price list
$I_n = I_u$ A		I_i A 	P kW	I_e A				
Short-circuit protection								
Motor protection in conjunction with overload relay								
• With short-circuit release • Without overload release								
3 pole								
Terminals standard, terminal screws as accessories								
	40	320...560	18.5	36	NZMB1-S40 265726		NZMN1-S40 265731	
	50	400...700	22	41	NZMB1-S50 265727		NZMN1-S50 265732	
	63	504...882	30	55	NZMB1-S63 265728		NZMN1-S63 265733	
	80	640...1120	37	68	NZMB1-S80 265729		NZMN1-S80 265734	
	100	800...1250	55	99	NZMB1-S100 265730		NZMN1-S100 265735	
Terminal screws standard, terminals as accessories								
	40	320...560	18.5	36				
	50	400...700	22	41				
	63	504...882	30	55				
	80	640...1120	37	68				
	100	800...1400	55	99				
	125	1000...1750	55	99	NZMB2-S125 265736		NZMN2-S125 265739	
	160	1280...2240	75	134	NZMB2-S160 265737		NZMN2-S160 265740	
	200	1600...2500	110	196	NZMB2-S200 265738		NZMN2-S200 265741	

http://catalog.moeller.net				Moeller HPL0211-2007/2008			
High switching capacity 100 kA at 415 V 50/60 Hz							
Part no. Article no.	Price see price list	Part no. Article no.	Price see price list	Std. pack	Notes		