



Powering Business Worldwide



## General specifications

PRODUCT NAME	Eaton Moeller® series PKE Trip block
CATALOG NUMBER	153164
MODEL CODE	PKE-XTUCP-36
EAN	4015081498918
PRODUCT LENGTH/DEPTH	41.6 mm
PRODUCT HEIGHT	64.2 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.09 kg
CERTIFICATIONS	VDE 0660 IEC/EN 60947
CATALOG NOTES	This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures.

## Features & Functions

### FUNCTIONS

Short-circuit protection  
Line and cable protection  
System protection  
Overcurrent protection

### NUMBER OF POLES

Three-pole

## General

### CURRENT FLOW TIMES - MIN

1000 (Class 20) AC-4 cycle operation, Main conducting paths  
Note: Going below the minimum current flow time can cause overheating of the load (motor).  
For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.  
500 (Class 5) AC-4 cycle operation, Main conducting paths  
700 (Class 10) AC-4 cycle operation, Main conducting paths  
900 (Class 15) AC-4 cycle operation, Main conducting paths

### CUT-OUT PERIODS - MIN

≤ 500 ms, main conducting paths, AC-4 cycle operation

### DEGREE OF PROTECTION

Device: IP20  
Terminals: IP00

### OPERATING FREQUENCY

60 Operations/h

### OVERLOAD RELEASE CURRENT SETTING - MIN

15 A

### OVERLOAD RELEASE CURRENT SETTING - MAX

36 A

### OVERVOLTAGE CATEGORY

III

### POLLUTION DEGREE

3

### PRODUCT CATEGORY

Accessories

### PROTECTION

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

### RATED IMPULSE WITHSTAND VOLTAGE (UIMP)

6000 V AC

### TEMPERATURE COMPENSATION

-5 - 40 °C to IEC/EN 60947, VDE 0660  
-25 - 55 °C, Operating range

### VOLTAGE TYPE

Self powered

## Ambient conditions, mechanical

<b>SHOCK RESISTANCE</b>	25 g, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
-------------------------	---

## Climatic environmental conditions

<b>ALTITUDE</b>	Max. 2000 m
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	55 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

## Electrical rating

<b>RATED FREQUENCY - MIN</b>	50 Hz
------------------------------	-------

<b>RATED FREQUENCY - MAX</b>	60 Hz
------------------------------	-------

<b>RATED OPERATIONAL CURRENT (IE)</b>	36 A
---------------------------------------	------

<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	690 V
---	-------

<b>RATED UNINTERRUPTED CURRENT (IU)</b>	36 A
---	------

<b>SUPPLY VOLTAGE AT AC, 50 HZ - MIN</b>	690 V
--	-------

<b>SUPPLY VOLTAGE AT AC, 50 HZ - MAX</b>	690 V
--	-------

## Short-circuit rating

<b>SHORT-CIRCUIT RELEASE</b>	Delayed approx. 60 ms, Trip blocks 75 A - 288 A, I <sub>rm</sub> , Setting range ± 20% tolerance, Trip blocks Trip block adjustable 5 - 8 x I <sub>r</sub>
------------------------------	---

## Magnet system

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	0 V
---	-----

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	0 V
---	-----

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	0 V
---	-----

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	0 V
---	-----

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	0 V
--	-----

<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	0 V
--	-----

## Contacts

<b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>	0
--	---

<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b>	0
--	---

<b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
--	---

## Communication

<b>CONNECTION TO SMARTWIRE-DT</b>	No
-----------------------------------	----

## Design verification

<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	4.9 W
---	-------

<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
--	-----

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	1.7 W
--	-------

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	36 A
--	------

<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
---	-----

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
------------------------------------	--

<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
---	--

<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
---	--

<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
---	--

<b>10.2.4 RESISTANCE TO</b>	Meets the product
-----------------------------	-------------------

<b>ULTRA-VIOLET (UV) RADIATION</b>	standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the

instruction leaflet (IL) is  
observed.

## Resources

BROCHURES	<a href="#">eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf</a>
	<a href="#">eaton-motor-protective-circuit-breaker-pke-and-communication-modul-pke-brochure-w12107613en-en-us.pdf</a>
CATALOGUES	<a href="#">Product Range Catalog Switching and protecting motors</a>
	<a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-accessory-declaration-of-conformity-eu250706en.pdf</a>
	<a href="#">eaton-accessory-declaration-of-conformity-uk251189en.pdf</a>
DRAWINGS	<a href="#">eaton-manual-motor-starters-pke-trip-block-characteristic-curve-002-de.eps</a>
	<a href="#">eaton-manual-motor-starters-mounting-3d-drawing.eps</a>
	<a href="#">eaton-manual-motor-starters-pke-trip-block-3d-drawing-002.eps</a>
ECAD MODEL	<a href="#">ETN.153164.edz</a>
INSTALLATION INSTRUCTIONS	<a href="#">IL034013ZU</a>
INSTALLATION VIDEOS	<a href="#">Video Motor Protective Circuit Breaker PKE</a>
	<a href="#">WIN-WIN with push-in technology</a>
MANUALS AND USER GUIDES	<a href="#">eaton-motor-protection-pke12-32-65-mn03402004z-de-de-en-us.pdf</a>
MCAD MODEL	<a href="#">DA-CS-pke_xtu12</a>
	<a href="#">DA-CD-pke_xtu12</a>
SALES NOTES	<a href="#">eaton-pke-modbus-rtu-modul-flyer-fl034008en-en-us.pdf</a>

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

