

Specifications



Photo is representative



Eaton 051794

Eaton Moeller® series DILEM Contactor, 220 V 50 Hz, 240 V 60 Hz, 3 pole, 380 V 400 V, 4 kW, Contacts N/C = Normally closed= 1 NC, Screw terminals, AC operation

General specifications

PRODUCT NAME	Eaton Moeller® series DILEM Mini contactor
CATALOG NUMBER	051794
MODEL CODE	DILEM- 01(220V50HZ,240V60HZ)
EAN	4015080517948
PRODUCT LENGTH/DEPTH	52 mm
PRODUCT HEIGHT	58 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.17 kg
CERTIFICATIONS	CSA Class No.: 3211-04 CE IEC/EN 60947 IEC/EN 60947-4-1 VDE 0660 CSA File No.: 012528 UL 508 UL Category Control No.: NLDX UL File No.: E29096 CSA CSA-C22.2 No. 14-05 UL
CATALOG NOTES	Also tested according to AC-3e.



Powering Business Worldwide

Features & Functions

FEATURES

Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module

FITTED WITH:

Auxiliary contact

NUMBER OF POLES

Three-pole

General

APPLICATION

Mini Contactors for Motors and Resistive Loads

LIFESPAN, MECHANICAL

10,000,000 Operations
150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in series 0.5 A)
7,000,000 Operations (Coil 50/60 Hz)
200,000 Operations (at 240 V, AC-15)

MOUNTING POSITION

As required (except vertical with terminals A1/A2 at the bottom)

OPERATING FREQUENCY

9000 mechanical Operations/h

OVERVOLTAGE CATEGORY

III

POLLUTION DEGREE

3

PRODUCT CATEGORY

Contactors

PROTECTION

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)

6000 V AC

SHOCK RESISTANCE

10 g, N/C auxiliary contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
20 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
20 g, N/O auxiliary contact, Basic unit with auxiliary

	contact module, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
SUITABLE FOR	Also motors with efficiency class IE3
UTILIZATION CATEGORY	AC-3: Normal AC induction motors: starting, switch off during running
VOLTAGE TYPE	AC

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 1.5) mm ² 1 x (0.75 - 1.5) mm ²
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 2.5) mm ² 2 x (0.75 - 2.5) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14
STRIPPING LENGTH (MAIN CABLE)	8 mm
SCREWDRIVER SIZE	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver

Electrical rating

**RATED BREAKING
CAPACITY AT 220/230 V** 90 A

**RATED BREAKING
CAPACITY AT 380/400 V** 90 A

**RATED BREAKING
CAPACITY AT 500 V** 64 A

**RATED OPERATIONAL
POWER AT AC-3, 240 V, 50
HZ** 2.5 kW

**RATED OPERATIONAL
POWER AT AC-3, 380/400
V, 50 HZ** 4 kW

**RATED OPERATIONAL
POWER AT AC-3, 415 V, 50
HZ** 4.3 kW

**RATED BREAKING
CAPACITY AT 660/690 V** 42 A

**RATED MAKING
CAPACITY UP TO 440 V
(COS PHI TO IEC/EN
60947)** 110 A

**RATED OPERATIONAL
POWER AT AC-4, 220/230
V, 50 HZ** 1.5 kW

**RATED OPERATIONAL
POWER AT AC-4, 240 V, 50
HZ** 1.8 kW

**RATED OPERATIONAL
POWER AT AC-4, 415 V, 50
HZ** 3.1 kW

**RATED OPERATIONAL
POWER AT AC-4, 440 V, 50
HZ** 3.3 kW

**RATED OPERATIONAL
POWER AT AC-4, 500 V, 50
HZ** 3 kW

**RATED OPERATIONAL
POWER AT AC-4, 660/690
V, 50 HZ** 3 kW

**RATED OPERATIONAL
VOLTAGE (UE) AT AC -
MAX** 690 V

**RATED INSULATION
VOLTAGE (UI)** 690 V

**RATED OPERATIONAL
CURRENT (IE)** 0.5 A at 220 V, DC L/R ≤ 15
ms (with 3 contacts in
series)
2.5 A at 60 V, DC L/R ≤ 15
ms (with 2 contacts in
series)
1.5 A at 100 V, DC L/R ≤ 15

Short-circuit rating

**SHORT-CIRCUIT CURRENT
RATING (BASIC RATING)** 45 A, max. Fuse, SCCR
(UL/CSA)
5 kA, SCCR (UL/CSA)

SHORT-CIRCUIT PROTECTION

6 A gG/gL, Max. Fuse 500V,
Auxiliary contacts, Short-
circuit rating without
welding
PKZM0-4, Maximum
overcurrent protective
device, Short-circuit
protection only, Auxiliary
contacts, Short-circuit
rating without welding
10 A fast, Max. Fuse 500V,
Auxiliary contacts, Short-
circuit rating without
welding

**SHORT-CIRCUIT
PROTECTION RATING
(TYPE 1 COORDINATION)
AT 500 V** 20 A gG/gL

**SHORT-CIRCUIT
PROTECTION RATING
(TYPE 2 COORDINATION)
AT 500 V** 10 A gG/gL

	ms (with 3 contacts in series) 2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)
RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V	22 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	6 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	3 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	9 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	9 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V	9 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V	6.4 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V	4.8 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V	6.6 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V	6.6 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V	5 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V	3.4 A
RATED OPERATIONAL CURRENT (IE) AT DC-1, 110 V	20 A
RATED OPERATIONAL CURRENT (IE) AT DC-1, 12 V	20 A
RATED OPERATIONAL CURRENT (IE) AT DC-1, 220 V	20 A

RATED OPERATIONAL CURRENT (IE) AT DC-1, 24 V	20 A
RATED OPERATIONAL CURRENT (IE) AT DC-1, 60 V	20 A
SAFE ISOLATION	300 V AC, Between the contacts, According to EN 61140 300 V AC, Between coil and auxiliary contacts, According to EN 61140 300 V AC, Between auxiliary contacts, According to EN 61140 300 V AC, Between coil and contacts, According to EN 61140

Conventional thermal current I _{th}	
CONVENTIONAL THERMAL CURRENT I_{TH} (1-POLE, ENCLOSED)	40 A
CONVENTIONAL THERMAL CURRENT I_{TH} (3-POLE, ENCLOSED)	16 A
CONVENTIONAL THERMAL CURRENT I_{TH} AT 55°C (3-POLE, OPEN)	19 A
CONVENTIONAL THERMAL CURRENT I_{TH} OF AUXILIARY CONTACTS (1-POLE, OPEN)	10 A
CONVENTIONAL THERMAL CURRENT I_{TH} OF MAIN CONTACTS (1- POLE, OPEN)	50 A

Switching capacity	
SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	15 A, Maximum motor rating (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	0.5 A, 250 V DC, (UL/CSA) 10 A, 600 V AC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)

Magnet system

ARCING TIME	12 ms at 690 V AC
CHANGEOVER TIME	16 - 21 ms
DUTY FACTOR	100 %
PICK-UP VOLTAGE	1.1 V AC x U _c (voltage tolerance - dual frequency coil 50/60 Hz) 0.8 - 1.1 V AC x U _c (voltage tolerance - single-voltage coil 50 Hz and dual-voltage coil 50 Hz, 60 Hz)
POWER CONSUMPTION, PICK-UP, 50 HZ	22 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz 25 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
POWER CONSUMPTION, PICK-UP, 60 HZ	22 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz 25 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
POWER CONSUMPTION, SEALING, 50 HZ	1.8 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz 4.6 VA, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
POWER CONSUMPTION, SEALING, 60 HZ	1.8 W, AC, Single-frequency coil 50 Hz and Dual-frequency coil 50/60 Hz
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	220 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	220 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	0 V
RATED CONTROL SUPPLY	0 V

Motor rating

ASSIGNED MOTOR
POWER AT 115/120 V, 60 HZ, 1-PHASE 0.5 HP

ASSIGNED MOTOR
POWER AT 200/208 V, 60 HZ, 3-PHASE 2 HP

ASSIGNED MOTOR
POWER AT 230/240 V, 60 HZ, 1-PHASE 1.5 HP

ASSIGNED MOTOR
POWER AT 230/240 V, 60 HZ, 3-PHASE 3 HP

ASSIGNED MOTOR
POWER AT 460/480 V, 60 HZ, 3-PHASE 5 HP

ASSIGNED MOTOR
POWER AT 575/600 V, 60 HZ, 3-PHASE 5 HP

VOLTAGE (US) AT DC - MAX	
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN	14 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX	21 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MIN	8 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	18 ms
SWITCHING TIME (AC OPERATED, N/O, WITH AUXILIARY CONTACT MODULE, CLOSING DELAY)	45 ms

Contacts	
CONTROL CIRCUIT RELIABILITY	< 2 λ , < 1 failure at 100,000,000 Operations (at $U_e = 24$ V DC, $U_{min} = 17$ V, $I_{min} = 5.4$ mA)
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0

Design verification	
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	1.2 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.4 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	9 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.8 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE	Meets the product standard's requirements.

BY INTERNAL ELECT. EFFECTS	
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION**

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf Product Range Catalog Switching and protecting motors
CHARACTERISTIC CURVE	eaton-contactors-component-dilm-characteristic-curve-003.eps eaton-contactors-short-time-loading-dilm-characteristic-curve.eps eaton-contactors-switch-dilm-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	eaton-mini-contactor-declaration-of-conformity-uk251242en.pdf eaton-mini-contactor-declaration-of-conformity-eu250759en.pdf
DRAWINGS	eaton-contactors-diler-dimensions-005.eps eaton-contactors-diler-dimensions-004.eps eaton-contactors-dilem-dimensions.eps eaton-tripping-devices-mounting-diler-contactor-relay-symbol.eps eaton-general-ie-ready-dilm-contactor-standards.eps
ECAD MODEL	ETN.051794.edz
INSTALLATION INSTRUCTIONS	IL03407009Z
MCAD MODEL	DA-CS-dil_em DA-CD-dil_em
PEP ECO-PASSPORT	eaton-iec-contactors-pep-eato-00133-v0101-en.pdf
SYSTEM OVERVIEW	eaton-contactors-accessory-dilem-system-overview.eps
WIRING DIAGRAMS	eaton-contactors-contact-dilm-wiring-diagram-002.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

