Specifications



Eaton 203599

Eaton Moeller® series PKZ0 Sealing facility

General specifications		
PRODUCT NAME	Eaton Moeller® series PKZ0 Accessory Sealable cover	
CATALOG NUMBER	203599	
EAN	4015082035990	
PRODUCT LENGTH/DEPTH	33 mm	
PRODUCT HEIGHT	6 mm	
PRODUCT WIDTH	12 mm	
PRODUCT WEIGHT	2 g	
CERTIFICATIONS	Request filed for UL and CSA	
MODEL CODE	PL-PKZ0	



Features & Functions		General	
To prevent tampering with the overload release and the test function, it can be sealed using industry	ACCESSORY/SPARE PART TYPE	Cover	
	PRODUCT CATEGORY	Accessories	

Climatic environmental conditions	
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C

standard sealing wire

Design verification	
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.	
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.	
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.	
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.	
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.	
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.	
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.	
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.	
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.	
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.	
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.	
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is	

Resources	
BROCHURES	eaton-motor-starters- system-xstart-brochure- br03407001en-en-us.pdf
CATALOGUES	eaton-product-overview- for-machinery-catalogue- ca08103003zen-en-us.pdf Product Range Catalog Switching and protecting motors
DRAWINGS	<u>1210DRW-619</u>
ECAD MODEL	DA-CE-ETN.PL-PKZ0
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	pl_pkz0.dwg pl_pkz0.stp
SALES NOTES	eaton-link-module-for- motor-starters-pkz-flyer- fl034003en-en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









