

# Specifications

## Eaton 255895

Eaton Moeller® series P1 Main switch, P1, 32 A, surface mounting, 3 pole, 1 N/O, 1 N/C, STOP function, With black rotary handle and locking ring, UL/CSA

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series P1 Main switch
<b>CATALOG NUMBER</b>	255895
<b>EAN</b>	4015082558956
<b>PRODUCT LENGTH/DEPTH</b>	115 mm
<b>PRODUCT HEIGHT</b>	180 mm
<b>PRODUCT WIDTH</b>	100 mm
<b>PRODUCT WEIGHT</b>	0.483 kg
<b>CERTIFICATIONS</b>	UL Listed CSA Class No.: 3211-05 CSA CSA-C22.2 No. 60947-4-1-14 CE CSA File No.: 012528 IEC/EN 60947-3 UL File No.: E36332 VDE 0660 IEC/EN 60204 IEC/EN 60947 UL UL 60947-4-1 UL Category Control No.: NLRV CSA-C22.2 No. 94
<b>MODEL CODE</b>	P1-32/I2/SVB-SW/HI11-NA



Powering Business Worldwide

## Features & Functions

<b>FEATURES</b>	Version as main switch Version as maintenance- /service switch
<b>FITTED WITH:</b>	Black rotary handle and locking ring
<b>FUNCTIONS</b>	STOP function Interlockable
<b>NUMBER OF POLES</b>	3

## General information

<b>ACCESSORIES</b>	Auxiliary contact or neutral conductor fitted by user.
<b>DEGREE OF PROTECTION</b>	NEMA 12
<b>DEGREE OF PROTECTION (FRONT SIDE)</b>	IP65
<b>LIFESPAN, MECHANICAL</b>	300,000 Operations
<b>MOUNTING METHOD</b>	Surface mounting
<b>MOUNTING POSITION</b>	As required
<b>OPERATING FREQUENCY</b>	1200 Operations/h
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	3
<b>PRODUCT CATEGORY</b>	Main switch
<b>PRODUCT CATEGORY</b>	Main switch
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	6000 V AC
<b>SAFE ISOLATION</b>	440 V AC, Between the contacts, According to EN 61140
<b>SAFETY PARAMETER (EN ISO 13849-1)</b>	B10d values as per EN ISO 13849-1, table C.1
<b>SHOCK RESISTANCE</b>	15 g, Mechanical, According to IEC/EN 60068-2-27, Half- sinusoidal shock 20 ms
<b>SUITABLE FOR</b>	Branch circuits, suitable as motor disconnect, (UL/CSA) Ground mounting
<b>TYPE</b>	Main switch

## Climatic environmental conditions

<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
--	--------

<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	40 °C
--	-------

<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
---	--------

<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
---	-------

<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
--------------------------	--

## Terminal capacities

<b>TERMINAL CAPACITY</b>	2 x (1.5 - 6) mm <sup>2</sup> , solid or stranded 14 - 8 AWG, solid or flexible with ferrule 1 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228 1 x (1.5 - 6) mm <sup>2</sup> , solid or stranded 2 x (1 - 4) mm <sup>2</sup> , flexible with ferrules to DIN 46228
--------------------------	--

<b>SCREW SIZE</b>	M4, Terminal screw
-------------------	--------------------

<b>TIGHTENING TORQUE</b>	1.6 Nm, Screw terminals 14.1 lb-in, Screw terminals
--------------------------	--

## Electrical rating

**RATED BREAKING  
CAPACITY AT 220/230 V  
(COS PHI TO IEC 60947-3)** 260 A

**RATED BREAKING  
CAPACITY AT 400/415 V  
(COS PHI TO IEC 60947-3)** 300 A

**RATED BREAKING  
CAPACITY AT 500 V (COS  
PHI TO IEC 60947-3)** 290 A

**RATED BREAKING  
CAPACITY AT 660/690 V  
(COS PHI TO IEC 60947-3)** 250 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
220 V, 230 V, 240 V** 26.4 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
380 V, 400 V, 415 V** 26.4 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
500 V** 23.4 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-3,  
660 V, 690 V** 14.7 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-21,  
440 V** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
230 V** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
400 V, 415 V** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
500 V** 30 A

**RATED OPERATIONAL  
CURRENT (IE) AT AC-23A,  
690 V** 19.8 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-1,  
LOAD-BREAK SWITCHES  
L/R = 1 MS** 32 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-23A,  
24 V** 25 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-23A,  
48 V** 25 A

**RATED OPERATIONAL  
CURRENT (IE) AT DC-23A,** 25 A

## Short-circuit rating

**RATED CONDITIONAL  
SHORT-CIRCUIT CURRENT  
(IQ)** 80 kA

**RATED SHORT-TIME  
WITHSTAND CURRENT  
(ICW)** 640 A, Contacts, 1 second  
0.64 kA

**SHORT-CIRCUIT CURRENT  
RATING (BASIC RATING)** 5 kA, SCCR (UL/CSA)  
110A, max. Fuse, SCCR  
(UL/CSA)

**SHORT-CIRCUIT CURRENT  
RATING (HIGH FAULT)** 10 kA, SCCR (UL/CSA)  
50 A, Class J, max. Fuse,  
SCCR (UL/CSA)

**SHORT-CIRCUIT  
PROTECTION RATING** 50 A gG/gL, Fuse, Contacts

<b>60 V</b>	
<b>RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V</b>	12 A
<b>RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ</b>	13 kW
<b>RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ</b>	13 kW
<b>RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ</b>	18.5 kW
<b>RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ</b>	15 kW
<b>RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ</b>	7.5 kW
<b>RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ</b>	15 kW
<b>RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ</b>	18.5 kW
<b>RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ</b>	15 kW
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	690 V
<b>RATED UNINTERRUPTED CURRENT (IU)</b>	32 A
<b>UNINTERRUPTED CURRENT</b>	Rated uninterrupted current I <sub>u</sub> is specified for max. cross-section.

## Switching capacity

LOAD RATING	1.3 x I <sub>e</sub> (with intermittent operation class 12, 60 % duty factor)
	1.6 x I <sub>e</sub> (with intermittent operation class 12, 40 % duty factor)
	2 x I <sub>e</sub> (with intermittent operation class 12, 25 % duty factor)

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V

1

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V

2

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V

2

### NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V

3

### SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)

30 A, Rated uninterrupted current max. (UL/CSA)

### SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)

10A, IU, (UL/CSA)

### SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)

P600 (UL/CSA)  
A600 (UL/CSA)

### RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)

320 A

### VOLTAGE PER CONTACT PAIR IN SERIES

60 V

## Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
-----------------------------	---

### NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)

0

### NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)

1

### NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)

1

## Motor rating

### ASSIGNED MOTOR

POWER AT 115/120 V, 60 HZ, 1-PHASE 1 HP

### ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 1-PHASE 2 HP

### ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 3-PHASE 3 HP

### ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 1-PHASE 3 HP

### ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 3-PHASE 7.5 HP

### ASSIGNED MOTOR

POWER AT 460/480 V, 60 HZ, 3-PHASE 10 HP

### ASSIGNED MOTOR

POWER AT 575/600 V, 60 HZ, 3-PHASE 15 HP

## Actuator

ACTUATOR COLOR Black

ACTUATOR TYPE Door coupling rotary drive

## Design verification

**EQUIPMENT HEAT  
DISSIPATION, CURRENT-  
DEPENDENT PVID** 1.8 W

**HEAT DISSIPATION  
CAPACITY PDISS** 0 W

**HEAT DISSIPATION PER  
POLE, CURRENT-  
DEPENDENT PVID** 1.8 W

**RATED OPERATIONAL  
CURRENT FOR SPECIFIED  
HEAT DISSIPATION (IN)** 32 A

**STATIC HEAT  
DISSIPATION, NON-  
CURRENT-DEPENDENT  
PVS** 0 W

**10.2.2 CORROSION  
RESISTANCE** Meets the product  
standard's requirements.

**10.2.3.1 VERIFICATION OF  
THERMAL STABILITY OF  
ENCLOSURES** Meets the product  
standard's requirements.

**10.2.3.2 VERIFICATION OF  
RESISTANCE OF  
INSULATING MATERIALS  
TO NORMAL HEAT** Meets the product  
standard's requirements.

**10.2.3.3 RESIST. OF  
INSUL. MAT. TO  
ABNORMAL HEAT/FIRE  
BY INTERNAL ELECT.  
EFFECTS** Meets the product  
standard's requirements.

**10.2.4 RESISTANCE TO  
ULTRA-VIOLET (UV)  
RADIATION** UV resistance only in  
connection with protective  
shield.

**10.2.5 LIFTING** Does not apply, since the  
entire switchgear needs to  
be evaluated.

**10.2.6 MECHANICAL  
IMPACT** Does not apply, since the  
entire switchgear needs to  
be evaluated.

**10.2.7 INSCRIPTIONS** Meets the product  
standard's requirements.

**10.3 DEGREE OF  
PROTECTION OF  
ASSEMBLIES** Does not apply, since the  
entire switchgear needs to  
be evaluated.

**10.4 CLEARANCES AND  
CREEPAGE DISTANCES** Meets the product  
standard's requirements.

**10.5 PROTECTION  
AGAINST ELECTRIC  
SHOCK** Does not apply, since the  
entire switchgear needs to  
be evaluated.

**10.6 INCORPORATION OF  
SWITCHING DEVICES AND  
COMPONENTS** Does not apply, since the  
entire switchgear needs to  
be evaluated.

<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

BROCHURES	<a href="#">Brochure - T Rotary Cam switch and P Switch-disconnector</a>
CATALOGUES	<a href="#">P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-main-switch-declaration-of-conformity-eu250806en.pdf</a> <a href="#">eaton-main-switch-declaration-of-conformity-uk251289en.pdf</a>
DRAWINGS	<a href="#">eaton-rotary-switches-p1-main-switch-dimensions-002.eps</a> <a href="#">eaton-rotary-switches-padlock-t0-main-switch-dimensions.eps</a> <a href="#">eaton-rotary-switches-t0-main-switch-symbol.eps</a>



	<a href="#">eaton-general-switch-t0-main-switch-symbol.eps</a> <a href="#">eaton-general-totally-insulated-t0-main-switch-symbol.eps</a>
ECAD MODEL	<a href="#">ETN.255895.edz</a>
INSTALLATION INSTRUCTIONS	<a href="#">eaton-switch-discon-p1-insulated-enclosure-il03802001z.pdf</a>
INSTALLATION VIDEOS	<a href="#">Eaton's P Switch-disconnectors used in a factory</a>
MCAD MODEL	<a href="#">DA-CD-bauform5</a> <a href="#">DA-CS-bauform5</a>
PRODUCT NOTIFICATIONS	<a href="#">MZ008005ZU_Orderform_Customized_Switch.pdf</a> <a href="#">MZ008006ZU_Orderform_Customized_Switch.pdf</a>
WIRING DIAGRAMS	<a href="#">eaton-rotary-switches-contact-p1-main-switch-wiring-diagram.eps</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

