

Specifications



Eaton DILM17-10(600V60HZ)

Eaton XT IEC mini contactor, 18A, 600 Vac, 60 Hz, 1NC, 18A, Frame C, 45 mm, 60 Hz, 2, 3/ 5, 5, 10, 15 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Screw terminals, Full voltage non-reversing miniature contactor, 400V, 7.5 kW

Photo is representative



General specifications

PRODUCT NAME	Eaton XT IEC mini contactor
CATALOG NUMBER	DILM17-10(600V60HZ)
PRODUCT LENGTH/DEPTH	138 mm
PRODUCT HEIGHT	85 mm
PRODUCT WIDTH	56.3 mm
PRODUCT WEIGHT	0.48 kg
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	CSA Certified UL Listed IEC 60947-4-1 EN 60947-4-1

Product specifications

AMPERAGE RATING	18A
HP RATING - MAX	2, 3/ 5, 5, 10, 15 (1/3PH @120,240/208,240, 480, 600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing miniature contactor
VOLTAGE RATING	400 V
FREQUENCY RATING	60 Hz
CONNECTION	Screw connection
FRAME SIZE	45 mm
TERMINALS	Screw terminals
OPERATING TEMPERATURE - MAX	60 °C
OPERATING TEMPERATURE - MIN	-25 °C
COIL VOLTAGE	600 Vac, 60 Hz
CONTACT CONFIGURATION	1 NC
CONTINUOUS AMPERE RATING	18 A
SERIES	XT IEC
NUMBER OF CONTACTS	1 NC
OPERATION	Non-reversing
POWER CONSUMPTION	7.5 kW

Resources

BROCHURES	C440 Electronic Overload Relay
MULTIMEDIA	S1, E4. Ask the Experts - NEMA, IEC and DP contactors Contactors Explained

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

