

# Specifications

Photo is representative



## Eaton 277032

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 7.5 kW, 1 NC, 42 V 50 Hz, 48 V 60 Hz, AC operation, Screw terminals DILM17-01(42V50HZ,48V60HZ)

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series DILM contactor
<b>CATALOG NUMBER</b>	277032
<b>MODEL CODE</b>	DILM17-01(42V50HZ,48V60HZ)
<b>EAN</b>	4015082770327
<b>PRODUCT LENGTH/DEPTH</b>	97 mm
<b>PRODUCT HEIGHT</b>	85 mm
<b>PRODUCT WIDTH</b>	45 mm
<b>PRODUCT WEIGHT</b>	0.428 kg
<b>CERTIFICATIONS</b>	UL 508 UL Category Control No.: NLDX CSA CE IEC/EN 60947 IEC/EN 60947-4-1 UL CSA-C22.2 No. 14-05 CSA File No.: 012528 CSA Class No.: 2411-03, 3211-04 VDE 0660 UL File No.: E29096
<b>CATALOG NOTES</b>	Contacts according to EN 50012

## Features & Functions

<b>FITTED WITH:</b>	Mirror contact
<b>NUMBER OF POLES</b>	Three-pole
<b>NUMBER OF POLES</b>	Three-pole
<b>NUMBER OF POLES</b>	Three-pole

## General information

<b>APPLICATION</b>	Contactors for Motors
<b>CONNECTION</b>	Screw terminals
<b>FRAME SIZE</b>	FS2
<b>LIFESPAN, MECHANICAL</b>	10,000,000 Operations (AC operated)
<b>OPERATING FREQUENCY</b>	5000 mechanical Operations/h (AC operated)
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	3
<b>PRODUCT CATEGORY</b>	Contactors
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	8000 V AC
<b>RESISTANCE PER POLE</b>	2.7 mΩ
<b>SUITABLE FOR</b>	Also motors with efficiency class IE3
<b>UTILIZATION CATEGORY</b>	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching
<b>VOLTAGE TYPE</b>	AC

## Ambient conditions, mechanical

### SHOCK RESISTANCE

5.3 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
 6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
 3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

## Climatic environmental conditions

<b>ALTITUDE</b>	Max. 2000 m
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

## Electro magnetic compatibility

**EMITTED INTERFERENCE** According to EN 60947-1

**INTERFERENCE IMMUNITY** According to EN 60947-1

## Terminal capacities

<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	2 x (0.75 - 10) mm <sup>2</sup> , Main cables 1 x (0.75 - 16) mm <sup>2</sup> , Main cables 1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables
<b>TERMINAL CAPACITY (SOLID)</b>	2 x (0.75 - 10) mm <sup>2</sup> , Main cables 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 4) mm <sup>2</sup> , Control circuit cables 1 x (0.75 - 16) mm <sup>2</sup> , Main cables
<b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>	Single 18 - 6, double 18 - 8, Main cables 18 - 14, Control circuit cables
<b>TERMINAL CAPACITY (STRANDED)</b>	1 x 16 mm <sup>2</sup> , Main cables
<b>STRIPPING LENGTH</b>	10 mm

<b>(MAIN CABLE)</b>	
<b>STRIPPING LENGTH (CONTROL CIRCUIT CABLE)</b>	10 mm
<b>SCREW SIZE</b>	M3.5, Terminal screw, Control circuit cables M5, Terminal screw, Main cables
<b>SCREWDRIVER SIZE</b>	2, Terminal screw, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
<b>TIGHTENING TORQUE</b>	1.2 Nm, Screw terminals, Control circuit cables 3.2 Nm, Screw terminals, Main cables

## Electrical rating

<b>RATED BREAKING CAPACITY AT 220/230 V</b>	170 A
<b>RATED BREAKING CAPACITY AT 380/400 V</b>	170 A
<b>RATED BREAKING CAPACITY AT 500 V</b>	170 A
<b>RATED BREAKING CAPACITY AT 660/690 V</b>	120 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V</b>	40 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V</b>	18 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V</b>	18 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V</b>	18 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V</b>	18 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V</b>	12 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V</b>	10 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V</b>	10 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V</b>	10 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V</b>	8 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-1, 60 V</b>	35 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-1, 110 V</b>	35 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-1, 220 V</b>	35 A
<b>RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947)</b>	238 A

## Short-circuit rating

<b>SHORT-CIRCUIT CURRENT RATING (BASIC RATING)</b>	125 A, max. Fuse, SCCR (UL/CSA) 125 A, max. CB, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA)
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)</b>	125/70 A, Class J, max. Fuse, SCCR (UL/CSA) 10/65 kA, CB, SCCR (UL/CSA) 10/100 kA, Fuse, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA)
<b>SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)</b>	10/100 kA, Fuse, SCCR (UL/CSA) 10/22 kA, CB, SCCR (UL/CSA) 125/70 A, Class J, max. Fuse, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA)
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V</b>	63 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V</b>	50 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V</b>	35 A gG/gL
<b>SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V</b>	35 A gG/gL

<b>RATED OPERATIONAL POWER AT AC-3, 240 V, 50 HZ</b>	5.5 kW
<b>RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ</b>	7.5 kW
<b>RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ</b>	10 kW
<b>RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ</b>	10.5 kW
<b>RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ</b>	12 kW
<b>RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ</b>	11 kW
<b>RATED OPERATIONAL POWER AT AC-4, 220/230 V, 50 HZ</b>	2.5 kW
<b>RATED OPERATIONAL POWER AT AC-4, 240 V, 50 HZ</b>	3 kW
<b>RATED OPERATIONAL POWER AT AC-4, 415 V, 50 HZ</b>	5 kW
<b>RATED OPERATIONAL POWER AT AC-4, 440 V, 50 HZ</b>	5.5 kW
<b>RATED OPERATIONAL POWER AT AC-4, 500 V, 50 HZ</b>	6 kW
<b>RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ</b>	6.5 kW
<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	690 V
<b>RATED INSULATION VOLTAGE (UI)</b>	690 V

## Conventional thermal current I<sub>th</sub>

<b>CONVENTIONAL THERMAL CURRENT I<sub>TH</sub> (1-POLE, ENCLOSED)</b>	80 A
---	------

<b>CONVENTIONAL THERMAL CURRENT I<sub>TH</sub> (3-POLE, ENCLOSED)</b>	32 A
---	------

<b>CONVENTIONAL THERMAL CURRENT I<sub>TH</sub> AT 55°C (3-POLE, OPEN)</b>	37 A
---	------

<b>CONVENTIONAL THERMAL CURRENT I<sub>TH</sub> AT 60°C (3-POLE, OPEN)</b>	35 A
---	------

<b>CONVENTIONAL THERMAL CURRENT I<sub>TH</sub> OF MAIN CONTACTS (1- POLE, OPEN)</b>	88 A
---	------

## Switching capacity

<b>SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)</b>	40 A, Maximum motor rating (UL/CSA)
--	--

<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)</b>	10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
---	---

<b>SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)</b>	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
--	--

## Magnet system

<b>ARCING TIME</b>	10 ms
<b>DROP-OUT VOLTAGE</b>	AC operated: 0.6 - 0.3 x Uc, AC operated
<b>DUTY FACTOR</b>	100 %
<b>PICK-UP VOLTAGE</b>	0.8 - 1.1 V AC x Uc
<b>POWER CONSUMPTION, PICK-UP, 50 HZ</b>	52 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz
<b>POWER CONSUMPTION, PICK-UP, 60 HZ</b>	67 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz
<b>POWER CONSUMPTION, SEALING, 50 HZ</b>	2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz 7.1 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz
<b>POWER CONSUMPTION, SEALING, 60 HZ</b>	2.1 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz 8.7 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN</b>	42 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX</b>	42 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN</b>	48 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX</b>	48 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>	0 V
<b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>	0 V
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MIN</b>	16 ms
<b>SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX</b>	22 ms
<b>SWITCHING TIME (AC OPERATED, MAKE</b>	8 ms

## Motor rating

**ASSIGNED MOTOR**  
**POWER AT 115/120 V, 60 HZ, 1-PHASE** 2 HP

**ASSIGNED MOTOR**  
**POWER AT 200/208 V, 60 HZ, 3-PHASE** 5 HP

**ASSIGNED MOTOR**  
**POWER AT 230/240 V, 60 HZ, 1-PHASE** 3 HP

**ASSIGNED MOTOR**  
**POWER AT 230/240 V, 60 HZ, 3-PHASE** 5 HP

**ASSIGNED MOTOR**  
**POWER AT 460/480 V, 60 HZ, 3-PHASE** 10 HP

**ASSIGNED MOTOR**  
**POWER AT 575/600 V, 60 HZ, 3-PHASE** 15 HP



CONTACTS, OPENING DELAY) - MIN	
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	14 ms

## Communication

CONNECTION TO SMARTWIRE-DT	No
-------------------------------	----

## Safety

SAFE ISOLATION	440 V AC, Between coil and contacts, According to EN 61140 440 V AC, Between the contacts, According to EN 61140
----------------	---

## Contacts

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
---	---

NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT	0
--	---

## Special purpose ratings

SPECIAL PURPOSE RATING OF BALLAST ELECTRICAL DISCHARGE LAMPS	40 A (600V 60Hz 3phase, 347V 60Hz 1phase) 40 A (480V 60Hz 3phase, 277V 60Hz 1phase)
---	--

SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING	18 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 108 A, LRA 480 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA)
---	--

SPECIAL PURPOSE RATING OF ELEVATOR CONTROL	11 A, 600 V 60 Hz 3-ph, (UL/CSA) 3 HP, 200 V 60 Hz 3-ph, (UL/CSA) 11 A, 200 V 60 Hz 3-ph, (UL/CSA) 3 HP, 240 V 60 Hz 3-ph, (UL/CSA) 9.6 A, 240 V 60 Hz 3-ph, (UL/CSA) 11 A, 480 V 60 Hz 3-ph, (UL/CSA) 7.5 HP, 480 V 60 Hz 3-ph, (UL/CSA) 10 HP, 600 V 60 Hz 3-ph, (UL/CSA)
--	--

SPECIAL PURPOSE RATING OF REFRIGERATION CONTROL (CSA ONLY)	240 A, LRA 480 V 60 Hz 3phase; (CSA) 180 A, LRA 600 V 60 Hz 3phase; (CSA) 30 A, FLA 600 V 60 Hz
---	---

	3phase; (CSA) 40 A, FLA 480 V 60 Hz 3phase; (CSA)
<b>SPECIAL PURPOSE RATING OF RESISTANCE AIR HEATING</b>	40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA) 40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
<b>SPECIAL PURPOSE RATING OF TUNGSTEN INCANDESCENT LAMPS</b>	40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA) 40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

## Design verification

<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	2.1 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0.7 W
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	18 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	2.1 W
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.

## Resources

	<a href="#">Product Range Catalog Switching and protecting motors</a>
CATALOGUES	<a href="#">SmartWire-DT Catalog</a> <a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>
CHARACTERISTIC CURVE	<a href="#">eaton-contactors-switch-dilm-characteristic-curve-002.eps</a> <a href="#">eaton-contactors-component-dilm-characteristic-curve-003.eps</a> <a href="#">eaton-contactors-switch-dilm-characteristic-curve.eps</a>
DECLARATIONS OF CONFORMITY	<a href="#">eaton-contactor-declaration-of-conformity-eu250735en.pdf</a> <a href="#">eaton-contactor-declaration-of-conformity-uk251218en.pdf</a>
DRAWINGS	<a href="#">eaton-contactors-dimensions-210t014.eps</a> <a href="#">eaton-contactors-mounting-dilm-dimensions-002.eps</a> <a href="#">eaton-contactors-mounting-dilm-dimensions.eps</a> <a href="#">eaton-contactors-contact-dimensions-210x202.eps</a> <a href="#">eaton-contactors-dilm-3d-drawing-009.eps</a> <a href="#">eaton-general-ie-ready-dilm-contactor-standards.eps</a>
ECAD MODEL	<a href="#">ETN.277032.edz</a>
INSTALLATION INSTRUCTIONS	<a href="#">IL03407014Z2021_09.pdf</a>
INSTALLATION VIDEOS	<a href="#">WIN-WIN with push-in technology</a>
MCAD MODEL	<a href="#">DA-CS-dil_m17_38</a> <a href="#">DA-CD-dil_m17_38</a>

<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

PEP ECO-PASSPORT	<a href="#">eaton-iec-contactors-pep-eato-00124-v0101-en.pdf</a>
SYSTEM OVERVIEW	<a href="#">eaton-contactors-dilm-contactor-system-overview.eps</a>
WIRING DIAGRAMS	<a href="#">2100SWI-117</a>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

