## Specifications



## Photo is representative





## Eaton XTOB035GC1

XT IEC Bimetallic Overload Relay, 25-35A overload range, 90 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 80-170A contactor, 10A trip type

| General specifications |   |
|------------------------|---|
| PRODUCT NAME           | Eaton XT IEC bimetallic overload relay              |
| CATALOG NUMBER         | XTOB035GC1  |
| COMPLIANCES            | RoHS Compliant<br>ATEX Compliant<br>CE Marked       |
| CERTIFICATIONS         | UL Listed<br>CSA Certified<br>IEC 60947<br>EN 60947 |



| Resources                     |  |
|-------------------------------|--|
| BROCHURES                     | C440 Electronic Overload<br>Relay  |
| CATALOGS                      | Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1     |
| MULTIMEDIA                    | Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - XTOB035GC1   |

**PROJECT NAME: PROJECT NUMBER: PREPARED BY:** DATE:



**Eaton Corporation plc** Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









