

Specifications



Eaton XTOB035GC1S

Eaton XT IEC bimetallic overload relay, 25-35A overload range, 90 mm Frame size, 1NO-1NC contact configuration, Separate mounting, used with 80-170A contactor, 10A trip type

General specifications

PRODUCT NAME	Eaton XT IEC bimetallic overload relay
CATALOG NUMBER	XTOB035GC1S
EAN	4015082784676
PRODUCT LENGTH/DEPTH	5.28 in
PRODUCT HEIGHT	5.43 in
PRODUCT WIDTH	4.65 in
PRODUCT WEIGHT	5.5 lb
COMPLIANCES	ATEX Compliant RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947

Product specifications

OVERLOAD RANGE	25-35 A
FRAME SIZE	90 mm
MOUNTING	Separate

Resources

BROCHURES	C440 Electronic Overload Relay
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOB035GC1S

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

