

# Specifications



## Eaton XTOB070GC1

Eaton XT IEC bimetallic overload relay, 50-70A overload range, 90 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 80-170A contactor, 10A trip type

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC bimetallic overload relay
<b>CATALOG NUMBER</b>	XTOB070GC1
<b>EAN</b>	4015082784638
<b>PRODUCT LENGTH/DEPTH</b>	5.28 in
<b>PRODUCT HEIGHT</b>	5.43 in
<b>PRODUCT WIDTH</b>	4.65 in
<b>PRODUCT WEIGHT</b>	3.1 lb
<b>COMPLIANCES</b>	CE Marked ATEX Compliant RoHS Compliant
<b>CERTIFICATIONS</b>	UL Listed CSA Certified IEC 60947 EN 60947

## Product specifications

USED WITH	80-170A contactor
OVERLOAD RANGE	50-70 A
TYPE	XT IEC Bimetallic Overload Relay
FRAME SIZE	90 mm
CONTACT CONFIGURATION	1 NO, 1 NC
MOUNTING	Direct
TRIP TYPE	10 A

## Resources

BROCHURES	<a href="#">C440 Electronic Overload Relay</a>
CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
MULTIMEDIA	<a href="#">Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTOB070GC1</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

