

# Specifications



## Eaton XTOB125GC1

Eaton XT IEC bimetallic overload relay, 95-125A overload range, 90 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 80-170A contactor, 10A trip type

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC bimetallic overload relay
<b>CATALOG NUMBER</b>	XTOB125GC1
<b>EAN</b>	4015082784652
<b>PRODUCT LENGTH/DEPTH</b>	5.28 in
<b>PRODUCT HEIGHT</b>	5.43 in
<b>PRODUCT WIDTH</b>	4.65 in
<b>PRODUCT WEIGHT</b>	2.98 lb
<b>COMPLIANCES</b>	ATEX Compliant CE Marked RoHS Compliant
<b>CERTIFICATIONS</b>	UL Listed CSA Certified IEC 60947 EN 60947



Powering Business Worldwide

## Product specifications

OVERLOAD RANGE	95-125 A
----------------	----------

FRAME SIZE	90 mm
------------	-------

MOUNTING	Direct
----------	--------

## Resources

BROCHURES	<a href="#">C440 Electronic Overload Relay</a>
-----------	--

CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
----------	--

MULTIMEDIA	<a href="#">Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained</a>
------------	--

SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTOB125GC1</a>
-------------------------------	--

PROJECT NAME:
---------------

PROJECT NUMBER:
-----------------

PREPARED BY:
--------------

DATE:
-------



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
[Eaton.com](http://Eaton.com)

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

