

Specifications



Photo is representative



Eaton XTOBP24BC1

Eaton XT IEC bimetallic overload relay, 0.16-0.24A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 7-15A contactor, 10A trip type

General specifications

PRODUCT NAME	Eaton XT IEC bimetallic overload relay
CATALOG NUMBER	XTOBP24BC1
EAN	4015082784324
PRODUCT LENGTH/DEPTH	3.27 in
PRODUCT HEIGHT	1.89 in
PRODUCT WIDTH	1.77 in
PRODUCT WEIGHT	0.3 lb
COMPLIANCES	CE Marked RoHS Compliant ATEX Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

Product specifications

OVERLOAD RANGE	0.16-0.24 A
----------------	-------------

FRAME SIZE	45 mm
------------	-------

MOUNTING	Direct
----------	--------

Resources

BROCHURES	C440 Electronic Overload Relay
-----------	--

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
----------	--

MULTIMEDIA	Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained
------------	--

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOBP24BC1
-------------------------------	--

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

