


# Specifications



## Eaton XTOBP40BC1

Eaton XT IEC bimetallic overload relay, 0.24-0.4A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 7-15A contactor, 10A trip type

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC bimetallic overload relay
<b>CATALOG NUMBER</b>	XTOBP40BC1
<b>EAN</b>	4015082784331
<b>PRODUCT LENGTH/DEPTH</b>	3.27 in
<b>PRODUCT HEIGHT</b>	1.89 in
<b>PRODUCT WIDTH</b>	1.77 in
<b>PRODUCT WEIGHT</b>	0.3 lb
<b>COMPLIANCES</b>	RoHS Compliant ATEX Compliant CE Marked
<b>CERTIFICATIONS</b>	UL Listed CSA Certified IEC 60947 EN 60947
<b>CATALOG NOTES</b>	Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.



## Product specifications

OVERLOAD RANGE	0.24-0.4 A
----------------	------------

FRAME SIZE	45 mm
------------	-------

MOUNTING	Direct
----------	--------

## Resources

BROCHURES	<a href="#">C440 Electronic Overload Relay</a>
-----------	------------------------------------------------

CATALOGS	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
----------	--------------------------------------------------------------------------------------------

MULTIMEDIA	<a href="#">Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained</a>
------------	------------------------------------------------------------------------------------------------

SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - XTOBP40BC1</a>
-------------------------------	--------------------------------------------------------

PROJECT NAME:
---------------

PROJECT NUMBER:
-----------------

PREPARED BY:
--------------

DATE:
-------



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
[Eaton.com](http://Eaton.com)

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

