Specifications





Eaton XT IEC contactor, 7A, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NC, 7A, Frame B, 45 mm, 50-60 Hz, 0.25, 0.75, 1/1.5, 2, 3, 5 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Threepole, Screw terminals, Full voltage non-reversing contactor





General specifications		
PRODUCT NAME	Eaton XT IEC contactor	
CATALOG NUMBER	XTCE007B01A	
EAN	4015082765828	
PRODUCT LENGTH/DEPTH	3 in	
PRODUCT HEIGHT	2 in	
PRODUCT WIDTH	3 in	
PRODUCT WEIGHT	0.5 lb	
COMPLIANCES	RoHS Compliant CE Marked	
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947	
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)	



Product specifications		
AMPERAGE RATING	7A	
HP RATING - MAX	0.25, 0.75, 1/ 1.5, 2, 3, 5 hp (1/3PH @115,200,230/200,230,460,575 V)	
NUMBER OF POLES	Three-pole	
ТҮРЕ	Full voltage non-reversing contactor	
FREQUENCY RATING	50-60 Hz	
FRAME SIZE	45 mm	
TERMINALS	Screw terminals	
COIL VOLTAGE	110-120 Vac, 50/60 Hz	
CONTACT CONFIGURATION	1 NC	
CONTINUOUS AMPERE RATING	7 A	
SERIES	XT IEC	
OPERATION	Non-reversing	

Resources	
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE007B01A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.









