Specifications



Photo is representative





Eaton XTCE007B01B

Eaton XT IEC contactor, 7A, 220 Vac 50 Hz, 240 Vac 60 Hz, 1NC, 7A, Frame B, 45 mm, 50-60 Hz, 0.25, 0.75, 1/ 1.5, 2, 3, 5 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor

General specifications		
PRODUCT NAME	Eaton XT IEC contactor	
CATALOG NUMBER	XTCE007B01B	
EAN	4015082765842	
PRODUCT LENGTH/DEPTH	1.81 in	
PRODUCT HEIGHT	3.07 in	
PRODUCT WIDTH	2.76 in	
PRODUCT WEIGHT	0.5 lb	
COMPLIANCES	CE Marked RoHS Compliant	
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947	
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)	



Product specifications		
AMPERAGE RATING	7A	
HP RATING - MAX	0.25, 0.75, 1/ 1.5, 2, 3, 5 hp (1/3PH @115,200,230/200,230,460,575 V)	
NUMBER OF POLES	Three-pole	
ТҮРЕ	Full voltage non-reversing contactor	
FREQUENCY RATING	50-60 Hz	
FRAME SIZE	45 mm	
TERMINALS	Screw terminals	
COIL VOLTAGE	220-240 Vac, 50/60 Hz	
CONTACT CONFIGURATION	1 NC	
CONTINUOUS AMPERE RATING	7 A	
SERIES	XT IEC	
OPERATION	Non-reversing	

Resources	
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE007B01B
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com



information.



latest product and support

Follow us on social media to get the



